




	DUAL SMART SWITCH SWITCHBOX-D-DIN/BLEBOX Wi-Fi, 230 V AC	TRIPLE SMART LIGHT SWITCH ATLO-WB3-TUYA Wi-Fi, Tuya Smart	SMART DOOR AND PEDESTRIAN DOOR CONTROLLER DOORBOX/BLEBOX Wi-Fi, 12 ... 24 V DC/AC
			
	43.21 EUR 43.21 EUR	12.93 EUR 12.93 EUR	38.46 EUR 38.46 EUR
Application	switching devices on/off	Works with lighting - switching on/off	doors, pedestrian doors, lockers, drawers
Rated voltage	230 V AC	100 ... 240 V AC, 50 / 60 Hz	12 ... 24 V DC/AC
Maximal total load	2 x 1150 W (resistance load) / 2 x 150 W (inductive or capacitive load)	...	1150 W / 1150 VA
Total maximal current	2 x 5 A	...	5 A
Maximum power	...	300 W (for each output)	...
Number of inputs	2	...	3
Rated current	...	max. 10 A	...
Number of buttons	...	3	...
Number of outputs	2	3	1
Connector type	screw terminals	screw terminals	screw terminals
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Permissible relative humidity	...	≤ 80 %	...

Main features	<ul style="list-style-type: none"> • Two output modes: independent and push-pull • Local control by physical button, • schedule, • sunrise and sunset mode, • timer, • remote access, • voice control, • The ability to set the default status of the device after a power failure, • Energy consumption metering, • Power measurement, • Charts and measurement history • µWiFi technology support • Illuminated, color front panel with an additional control button 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication 	<ul style="list-style-type: none"> • Electric strike control - relay contact, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • door control input, • µWiFi technology support • Additional security option by logging in with username and password
Housing	Plastic (ABS), DIN, TS-35 rail mounting	Plastic	Plastic
"Index of Protection"	IP20	...	IP20
Color	White	White	Black
Operation temp	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C
Weight	0.06 kg	0.11 kg	0.036 kg
Dimensions	90 x 17.5 x 65 mm	87 x 86 x 41 mm	39 x 39 x 22 mm
Manufacturer / Brand	BleBox	...	BleBox
Guarantee	2 years	2 years	2 years