

| | IP CAMERA IPC-HFW2431S-S-0280B-S2 - 4 Mpx 2.8 mm DAHUA | TV OR MONITOR MOUNT BS-106S |
|-------------------------------------|---|---|
| |  |  |
| | 1596.73 DKK 1596.73 DKK | 60.92 DKK 60.92 DKK |
| Standard | TCP/IP | ... |
| Mounting standard | ... | VESA : 75, 100, 200, 400 x 200 |
| Sensor | 1/3 " Progressive Scan CMOS | ... |
| Matrix size | 4 Mpx | ... |
| Screen size range | ... | 23 " ... 42 " |
| Scanning system | Progressive | ... |
| Bearing capacity | ... | 45 kg |
| Distance from mounting surface | ... | 19 mm from wall |
| Tilt adjustment | ... | — |
| Horizontal rotation | ... | — |
| Rotation in the plane of the screen | ... | — |
| Resolution | 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p | ... |
| Lens | 2.8 mm | ... |
| View angle | <ul style="list-style-type: none"> • 102 ° (manufacturer data) • 100 ° (our tests result) | ... |
| Range of IR illumination | 30 m | ... |
| RS-485 interface | — | ... |
| Memory card slot | Micro SD memory cards up to 256GB support (possible local recording) | ... |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Alarm inputs / outputs | — | ... |
| Audio | — | ... |
| Bitrate | <ul style="list-style-type: none"> • 32 ... 6144 kbps - H.264 • 12 ... 6144 kbps - H.265 | ... |
| Main stream frame rate | 20 fps @ 4 Mpx 25 fps @ 3.7 Mpx | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |
| Network protocols | IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, IEEE 802.1x, Bonjour | ... |
| WEB Server | Built-in | ... |
| Max. number of on-line users | 20 | ... |
| ONVIF | 18.06 | ... |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | |
|-------------------------------|--|-------------------|
| Mobile phones support | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS | ... |
| Default IP address | 192.168.1.108 | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | 80, 37777 | ... |
| PC client access ports | 37777 | ... |
| Mobile client access ports | 37777 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream | ... |
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • IVS analysis : intrusion, crossing the line (tripwire) | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA | ... |
| Power consumption | < 5 W | ... |
| Housing | Compact - Metal | ... |
| Color | White | Black |
| "Index of Protection" | IP67 | ... |
| Operation temp | -40 °C ... 60 °C | ... |
| Weight | 0.48 kg | 1.45 kg |
| Dimensions | Ø 70 x 166 mm | 455 x 260 x 19 mm |
| Supported languages | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Italian | ... |
| Manufacturer / Brand | DAHUA | ... |
| Guarantee | 3 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00