



	<a href="#">MOUNTING SCREWS SM-6/RACK</a>	<a href="#">SWITCH POE CS4226-24ET-375 24-PORT SFP DAHUA</a>
		
	0.52 GBP 0.52 GBP	647.72 GBP 647.72 GBP
Application	Rack 19" / Rack 10"	...
Package includes	<ul style="list-style-type: none"> <li>• 4 x M6 screw,</li> <li>• 4 x cage nut,</li> <li>• 4 x plastic shoulder washer, which protects the varnish coating of panels from damage during tightening the screws</li> </ul>	...
Material	Steel galvanized	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 24 x RJ45 10/100 Base-T ( 2 x Hi-PoE (802.3bt) + 22 x PoE (802.3af/at) ),</li> <li>• 2 x port Combo: SFP (1000 Base-X) / RJ45 (10/100/1000 Base-T) - Uplink</li> </ul>
Management	...	✓
LED diodes	...	Link, PoE, Power, System, 50 % PoE, 80 % PoE, 100 % PoE
Transmission speed	...	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps : 24 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 : 2 RJ45 (Uplink) ports,</li> <li>• 1000 : 2 SFP (Uplink) ports</li> </ul>
Maximal output power	...	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports</li> <li>• 30 W / port PoE 802.3af/at - 3 ... 24 ports</li> </ul>
Maximal total power	...	375 W
MAC addresses table	...	8k
Operation modes	...	<ul style="list-style-type: none"> <li>• Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (DoLynk Care application)</li> <li>• PoE power mode : The device supports 8-pin power supply</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE</li> <li>• Loop Protection</li> <li>• Compliance with the LLDP protocol</li> <li>• Port Based VLAN : 32</li> <li>• Data Flow Control (802.3x)</li> <li>• DHCP client</li> <li>• RESET button</li> <li>• Can be mounted in a Rack 19" cabinet</li> </ul>
Certificates	...	CE
Protections	...	<ul style="list-style-type: none"> <li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> </ul>
Housing	...	Metal
Power supply	...	100 ... 240 V AC @ 47 ... 63 Hz
Power consumption	...	max. 400 W
Operation temp	...	-10 °C ... 55 °C
Weight	0.037 kg	2.56 kg
Dimensions	<ul style="list-style-type: none"> <li>• 19.9 mm - Total length</li> <li>• 15.5 mm - Thread length</li> </ul>	440 x 220 x 44 mm, RACK 19", 1U
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	5 years