




	<a href="#">MECHANICAL SPLICE WITH SC/APC CONNECTOR FAST-SC-APC</a>	<a href="#">PROGRAMMER ESP32 FOR MODULES OF THE ESP-WROOM-02 SERIES</a>	<a href="#">ANTENNA AMPLIFIER AB-011 DVB-T 5V</a>
			
	6.22 DKK 6.22 DKK	141.70 DKK 141.70 DKK	159.24 DKK 159.24 DKK
Fiber type	Single-mode	...	...
Frequency range	...	...	470 MHz ... 862 MHz
Connector type	SC-APC	...	...
Fiber diameter	125 µm	...	...
Gain	...	...	14 dB / 27 dB (switch)
S/N ratio	...	...	< 1 dB
Compatibility	...	ESP-WROOM-02D, ESP-WROOM-02U, ESP8684, ESP32 and others	...
Return loss	...	...	> 10 dB
Cable diameter	3 mm / 2 mm / 900 µm / 250 µm	...	...
Number of inputs/outputs	...	...	1 / 1
IMA3 60dB	...	...	108 dBµV
Amplifier shield	...	...	✓
Input/output impedance	...	...	75 Ω
Splice reuse	max. 5 times	...	...
Connectors type	...	<ul style="list-style-type: none"> <li>• 1 x micro USB socket,</li> <li>• Place of temporary installation of the board with spring pins (dedicated to ESP-WROOM-02D/02U),</li> <li>• 20 x goldpin plug - Leading out the pins</li> </ul>	"F"
Housing	...	...	die-cast housing mounted inside compact plastic enclosure
Mounting	...	...	on a mast or a wall
Output signal level	...	3.3 V	...
Operation temp	...	...	-20 °C ... 50 °C
Power output	...	3.3 V, 5 V	...
Main features	...	<ul style="list-style-type: none"> <li>• ON/OFF button,</li> <li>• RESET button,</li> <li>• PROGRAM button</li> </ul>	...
Power supply	...	5 V - from USB port	4.5 V ... 12 V DC
Weight	...	0.02 kg	0.170 kg
Dimensions	...	47 x 41 x 18 mm	108 x 90 x 44 mm
Guarantee	2 years	2 years	2 years