



	IP VANDALPROOF CAMERA DS-2CD2H23G2-IZS(2.8-12MM) ACUSENSE - 1080p - MOTOZOOM Hikvision	PROJECTOR MOUNT BRATECK-PRB-3
		
	406.78 EUR 406.78 EUR	17.52 EUR 17.52 EUR
Bearing capacity	...	10 kg
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Distance from mounting surface	...	130 or 440 or 750 or 1075 mm
Projector mounting holes distances	...	Ø 130 ... 320 mm
Tilt adjustment	...	-15 ° ... 15 °
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Horizontal rotation	...	360 °
Lens	2.8 ... 12 mm - Motozoom	...
View angle	107 ° ... 32 °	...
Range of IR illumination	40 m	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Compliance with the AAC standard • Noise suppression and echo cancellation 	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.64	...
Web browser access ports	80	...

PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization 	...
Main stream frame rate	25 fps @ 1080p	...
Main features	<ul style="list-style-type: none"> • Camera from AcuSense series • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Video output - BNC socket • Image rotation and mirror • Day/night mode • Configurable Privacy Zones • Sharpness - sharper image outlines • Smart motion detection (with recognizing people and vehicles) • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 920 mA 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 12.5 W @ PoE (802.3af) • ≤ 11 W @ 12 V DC 	...
Housing	Dome - Metal	...
Color	White	Silver
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.85 kg	2.1 kg
Dimensions	Ø 138 x 126 mm	max. Ø 320 x 1075 mm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	BRATECK
SAP Code	311313533	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00