



	FINAL SOCKET LE-764566 R-TV + 2xSAT Niloe LEGRAND	STANDING RACK CABINET EPRADO-R19-42U/600FW-BLUE	NVR APTI-N3212AI-16P-13 32 CHANNELS, 16 PoE
			
	17.22 EUR 17.22 EUR	459.50 EUR 459.50 EUR	312.34 EUR 312.34 EUR
Standard	TCP/IP
Internal width	...	19 "	...
Mount	Flush-mounted, Claw or screw mounting
Internal height	...	42 U	...
Supported resolutions	max. 12 Mpx - 4000 x 3000 px
Internal depth	...	545 mm (max)	...
Video outputs	1 pcs HDMI 4K 1 pcs VGA
External width	...	600 mm	...
TV frequency range	5 ... 68 MHz 120 ... 862 MHz
External height	...	2050 mm	...
External depth	...	600 mm	...
Radio frequency range	87.5 ... 108 MHz
Holes for fan coolers	...	—	...
Bearing capacity	...	1000 kg	...
SAT frequency range	950 ... 2400 MHz
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard
TV tap attenuation	1.5 dB
Audio inputs	1 pcs CINCH
Color	...	Black RAL9004	...
Radio tap attenuation	1.5 dB
Audio outputs	1 pcs CINCH
SAT tap attenuation	2.0 dB
Application	Niloe product series
Door	...	<ul style="list-style-type: none"> • Front: glass • Side: metal, snap-in • Rear: metal, hinges 	...

Image compression method	H.265+ / H.265 / H.264+ / H.264
Bitrate	320 Mbps
Supported hard drives	2 x 10 TB SATA
Recording modes	Manual, Sensor, Motion detection, Schedule
External storage devices backup	Records backup at (.avi) format to USB (pendrive)
Main features	...	<ul style="list-style-type: none"> • From the top there are 6 cable entries with dimensions of 270 x 65 mm and 6 with dimensions of 245 x 65 mm • The floor has 6 cable entries with dimensions of 375 x 60 mm • Removable side panels • Possibility to mount the door as left or right • Four rack rails for mounting devices (2x front, 2x rear) • 4 keys included • The cabinet is mounted on wheels to allow it to be moved or on 4 legs 	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p
Network interface	1 x RJ-45 10/100/1000 Base-TX
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
Network protocols	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE
ONVIF	✓
Default IP address	192.168.1.88
Default admin user / password	admin / 12345
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • Android: Free application BitVision, iOS: Free application iVMS320
Web browser access ports	80, 5000, 554

PC client access ports	80, 5000, 554
USB	<ul style="list-style-type: none"> • 1 pcs USB 2.0 • 1 pcs USB 3.0
Serial ports	—
Alarm inputs / outputs	4 / 1
PTZ control	IP Speed Dome Cameras
Motion Detection	Split the screen into zones : 22 x 18 motion zones
Intelligent image analysis	✓
Main features	<ul style="list-style-type: none"> • Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom
Mouse support	✓
IR remote controller in the set	—
Switch PoE	16-port PoE Switch built-in : 15 W / Channel - PoE (802.3af)
Maximum total switch load	200 W
Power supply	100 ... 240 V AC, 50 / 60 Hz
Power consumption	≤ 15 W (without HDD & PoE)
Operation temp	-10 °C ... 50 °C
Weight	0.098 kg	98 kg	2.55 kg
Dimensions	76 x 76 x 40 mm	...	380 x 323 x 51 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Ukrainian, Italian
Manufacturer / Brand	LEGRAND	EPRADO	APTI
Guarantee	2 years	3 years	2 years