



	<a href="#">UPS AT-UPS1500-LCD 1500 VA EAST</a>	<a href="#">BATTERY AKU- AA-2000/GC*P4 1.2 V Ni-MH HR6, AA Green Cell</a>
		
	160.22 EUR 160.22 EUR	7.23 EUR 7.23 EUR
Nominal power	900 W	...
Apparent Power	1500 VA	...
In package	...	<b>4 pcs The price for package</b>
Input voltage	230 V AC $\pm$ 25 %	...
Rated voltage	...	1.2 V
Battery capacity	...	2000 mAh
Input frequency	50 / 60 Hz (auto detection)	...
Battery type	...	Ni-MH
Output voltage	230 V AC $\pm$ 10 % (Approximated Sine Wave)	...
Size	...	HR6, AA
Output frequency	50 / 60 Hz $\pm$ 1 %	...
Voltage adjustment	—	...
Frequency adjustment	—	...
Transfer time	2 ... 7 ms (typical), max. 10 ms	...
Charging time (recover to 90% capacity)	6 ... 8 hours	...
Battery	2 pcs - 12V/8Ah	...
Estimated battery operation time	<ul style="list-style-type: none"> <li>• 37.5 minutes @ 100 W,</li> <li>• 19 minutes @ 200 W,</li> <li>• 11.5 minutes @ 300 W,</li> <li>• 4.5 minutes @ 500 W,</li> <li>• 1.5 minutes @ 800 W</li> </ul>	...
Number of outputs	3 pcs CEE 7/3 (Schuko)	...
Management software	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)	...
Protections	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overvoltage - RJ45</li> <li>• Overcharge protection</li> <li>• discharge protection</li> <li>• Output voltage filtering</li> <li>• DC filter to eliminate interferences - EMI/RFI</li> </ul>	...

Operation state indication	<ul style="list-style-type: none"> <li>• LCD display: operation mode, battery charging level, in/out voltage level,</li> <li>• Sound signaling</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Excellent microprocessor control guarantees high reliability</li> <li>• COLD START function for manual switch to the battery power supply</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Automatic battery charging in OFF mode</li> <li>• self test feature</li> <li>• 2 x RJ45 - Input / Output</li> <li>• Port USB 2.0 - Access from PC</li> <li>• Remote management - UPSmart application (included)</li> <li>• Configurable alarm</li> <li>• Built-in EMI, RFI filter</li> <li>• The device works with power supply adapters having Active Power Factor Correction (APFC)</li> </ul>	...
Application	<ul style="list-style-type: none"> <li>• network, servers, workstations</li> <li>• Surveillance Systems</li> <li>• small servers, DVRs, telecommunication equipment, VoIP working hardware, desktop computers, etc.</li> </ul>	...
Housing type	Tower	...
Operation temp. / Relative humidity	0 °C ... 40 °C / 20 ... 90 %	...
Weight	9.84 kg	0.03 kg
Dimensions	348 x 140 x 173 mm	...
Manufacturer / Brand	EAST	Green Cell
Guarantee	2 years	2 years