



	EXPANSION PLUG KW-6/3.5X50 KLIMAS	ACCESS POINT 4G+ LTE +ROUTER RUT361 2.4 GHz 300 Mbps Teltonika
		
	0.07 EUR 0.07 EUR	196.93 EUR 196.93 EUR
Frequency range	...	2.4 GHz
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized 	...
Drilling diameter	6 mm	...
Expansion plug length	30 mm	...
Antenna type	...	2x2 MIMO : 2 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Screw dimensions	Ø 3.5 x 50 mm, PZ-2	...
Standards	...	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick 	...
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)
LAN ports	...	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN
Transmitter power	...	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA
LED indicators	...	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator
Network type	...	4G, 3G
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓

Protections	...	<ul style="list-style-type: none"> • WPA3-EAP • WPA3-SAE • WPA2-Enterprise - PEAP • WPA2-PSK • AES-CCMP • WEP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering
Management interface	...	Web browser, Teltonika RMS application, SMS
Main features	...	<ul style="list-style-type: none"> • Support for IoT (Internet of Things) systems, • Ability to work as a Hotspot, • Support for VoIP technology, • Support for Mesh technology • SIM socket • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems
Power supply	...	<ul style="list-style-type: none"> • 12 V DC / 1.5 A (power adapter included) • 9 ... 30 V DC
Power consumption	...	≤ 4.7 W
Operation temp	...	-40 °C ... 75 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	...	0.25 kg
Dimensions	...	100 x 93 x 30 mm
Manufacturer / Brand	KLIMAS	Teltonika
Guarantee	2 years	2 years