




	CONNECTION BOX PUH-3P-M20T	CONNECTION BOX PHW-75X75/EPN IP67 Elektro-Plast	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-T2A21-0280B - 1080p 2.8 mm DAHUA
			
	6.22 EUR 6.22 EUR	4.36 EUR 4.36 EUR	55.14 EUR 55.14 EUR
Number of intakes	3	4 - Cable glands PG-16	...
Number of terminals	3 x 3 pcs
Standard	HD-CVI, HD-TVI, AHD, PAL
Voltage insulation	450 V
Sensor	1/2.7 " Progressive Scan CMOS
Matrix size	2.1 Mpx
Cable diameter	Ø 5 ... Ø 9 mm	10 ... 14 mm	...
Wire gauge	0.5 ... 4 mm ²
Main features	...	<ul style="list-style-type: none"> • Surface mount • Cover mounting with screws • The set includes a 5 x 4 mm² insert • Compliance with PN-EN 60670-1 standards 	...
Material	...	Non-halogen plastic	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p , 960 x 576 - 960H, PAL
Range of IR illumination	20 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm
View angle	<ul style="list-style-type: none"> • 103 ° (manufacturer data) • 100 ° (our tests result)
S/N ratio	> 65 dB
Video output	HD-CVI / HD-TVI / AHD / PAL, 1 Vpp / 75 Ω
Audio	—

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
OSD menu	OSD menu available via DAHUA recorder
Power supply	12 V DC / 220 mA
Power consumption	≤ 2.7 W
Housing	Dome, Aluminum
Color	...	Gray	White
Vandal-proof	—
"Index of Protection"	IP68	IP67	IP67
Operation temp	-40 °C ... 60 °C
Weight	0.27 kg
Dimensions	102 ... 110 x 66 ... 72 x 26 mm	85 x 85 x 41 mm - External dimensions , 75 x 75 x 33 mm - Internal dimensions	Ø 94 x 78 mm
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Italian
Manufacturer / Brand	...	Elektro-Plast	DAHUA
Guarantee	2 years	2 years	3 years