

	ANGULAR PLUG LE-50103 230 V 16 A LEGRAND	HDD ENCLOSURE Y-3035 UNITEK	IP CAMERA APTI-250C61-2812P - 1080p 2.8 ... 12 mm
			
	42.81 SEK 42.81 SEK	365.64 SEK 365.64 SEK	711.11 SEK 711.11 SEK
Standard	TCP/IP
Rated voltage	230 V / 50 Hz
Sensor	1/2.8 " Sony CMOS IMX290, STARVIS Back-illuminated
Maximal current load	16 A
Digital Image Processor	Hisilicon 3516C
Supported hard drives	...	1 x SATA III, 2.5 " / 3.5 "	...
Grounding	✓
Matrix size	2.1 Mpx
Electrical cable	max. 3 x 2.5 mm ²
Cable terminals	screw terminals
Plug type	CEE 7/6
Resolution	1920 x 1080 - 1080p
Outputs	...	1 x USB 3.1, max. 5 Gb/s	...
Operation state indication	...	LED diodes	...
Lens	2.8 ... 12 mm, 3 Mpx
View angle	• 85 ° ... 23 ° (manufacturer data) • 100 ° ... 38 ° (our tests result)
S/N ratio	> 52 dB
Range of IR illumination	60 m
IR illuminator power adjustment	Automatic
Image compression method	H.265 / H.265+ / H.264 / H.264+
Alarm inputs / outputs	—
Audio	External microphone input
Bitrate	24 ... 9472 kbps - H.264 14 ... 5632 kbps - H.265
Main stream frame rate	30 fps @ 1080p
Network interface	10/100 Base-T (RJ-45)
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
Default IP address	192.168.1.168
Default admin user / password	admin / admin
Web browser access ports	80
PC client access ports	80
WEB Server	Built-in

Mobile client access ports	80
Max. number of on-line users	10
Port ONVIF	80
ONVIF	2.4
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application FREEIP • iOS (iPhone): Free application FREEIP
RS-485 interface	—
Main features	<ul style="list-style-type: none"> • 3D-DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • F-DNR (Defog) - Reduction of image noise caused by precipitation • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Mirror - Mirror image • RESET button - on the cable
Power supply	...	12 V DC / 2 A (power adapter included)	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 620 mA
Power consumption	≤ 7.5 W
Housing	...	Desktop, Plastic	Compact, Metal
Color	White	...	Graphite
"Index of Protection"	IP66
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Operation temp	-20 °C ... 60 °C
Weight	0.032 kg	0.2 kg	1.02 kg
Dimensions	84 x 37 x 44 mm	183 x 117 x 35 mm	288 x 90 x 103 mm
Manufacturer / Brand	LEGRAND	UNITEK	APTI
Guarantee	2 years	2 years	2 years