



	ACCESS CONTROLLER ASC3202B DAHUA	CAMERA BRACKET PFA5300R DAHUA
		
	431.82 GBP 431.82 GBP	30.21 GBP 30.21 GBP
Number of served transitions	2	...
Neck diameter	...	Ø 122 mm
Support	Cooperation with the access control systems	...
Suitable for cameras	...	DAHUA - documentation for download below.
Material	...	Aluminum
Distance from mounting surface	...	45 mm
Number of supported readers	<ul style="list-style-type: none"> • 2 pcs RS-485, • 2 pcs Wiegand 	...
Battery backup support	—	...
Alarm inputs / outputs	2 / 2	...
Communication	<ul style="list-style-type: none"> • 3 x RS-485, • 2 x Wiegand 34/26, • 1 x Ethernet 10 / 100 Mbps (RJ-45) 	...
Network protocols	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI	...
Operation modes	<ul style="list-style-type: none"> • Main control mode • Sub control mode 	...

Main features	<ul style="list-style-type: none"> • Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control) • 1000 indexed users • Support up to 3000 finger prints • Memory of 5000 RFID cards • Support storage of 300 000 records • 128 General Purpose Schedules • Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above • Tamper protections • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Beep signal - Buzzer • White list, Black list • Web-Server built-in • Software update via network • Monitoring and configuration through network - SmartPSS Lite application • Power output 12 V DC / 1 A - supplying power to the lock • Support hardware I/O port configuration and export configuration diagrams • ONVIF compliance 	...
Power supply	<ul style="list-style-type: none"> • 12 V DC / 2.5 A • PoE (802.3at) 	...
Power consumption	<ul style="list-style-type: none"> • ≤ 2 W (standby) • max. 20.4 W @ 12 V (operation) • max. 14.4 W @ PoE (operation) 	...
Housing	Plastic (PC + ABS)	...
Color	White	White

IK rating	IK06	...
Operation temp	-10 °C ... 55 °C	...
Permissible relative humidity	5 % ... 95 % (non-condensing)	...
Weight	0.72 kg	0.34 kg
Dimensions	186 x 186 x 58 mm	Ø 122 x 45 mm
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years