





	CHALK LINE REEL ST-0-47-100 STANLEY	EXTERNAL CAMERA DISTRIBUTION POINT EXPERT-POE/OTD-82GSFP 8 PoE + 2 x SFP	CODE LOCK INT-SZ-BL SATEL
			
	16.14 CAD 16.14 CAD	473.31 CAD 473.31 CAD	65.93 CAD 65.93 CAD
Line length	30 m
Support	INTEGRA
Maximum current switched over by relay at DC 24V	max. 2 A
Application	<ul style="list-style-type: none"> • For use in masonry work, • Electrical works, such as marking lines for pipes, trays or lines for lighting lamps
LAN ports	...	<ul style="list-style-type: none"> • 8 x RJ45 10/100 Base-T (8 x PoE (802.3af/at)), • 2 x SFP (Uplink) 1000 Base-X 	...
Main features	<ul style="list-style-type: none"> • relay for electromagnetic lock/electric strike • door control input • Alarms: keypad hold-down PANIC, FIRE and AUX • Microswitch as tamper contact • LEDs indicating device operation state • Blue backlight of the keys
Housing	Aluminum, Waterproof
Management	...	—	...
Current consumption	max. 66 mA
LED diodes	...	Power, Link/Act, PoE	...
Manufacturer / Brand	STANLEY	...	SATEL
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 LAN & PoE ports, • 1000 Mbps : 2 SFP (Uplink) ports 	...
Maximal output power	...	30 W @ PoE (802.3af/at) - 1 ... 8 ports	...
Maximal total power	...	115 W	...
MAC addresses table	...	16k	...

Operation modes	...	<ul style="list-style-type: none"> • E - EXTEND mode - ports 1, 2, 3, 4, 5, 6, 7, 8 support transmission up to 250 m • V - VLAN mode, 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • P - PoE Auto-check mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected 	...
Number of line cables	...	2	...
Number of splice cassettes	...	1	...
Splice capacity	...	8	...
Connector type	...	SC / PC	...
Number of adapters	...	4	...
Number of pigtails	...	4	...
Material	...	Metal	...
Color	...	Gray	...
"Index of Protection"	...	IP55	...
Cable entries	...	3 pcs from the bottom Ø 39 mm	...
Main features	<ul style="list-style-type: none"> • Universal hook at the end of the line • Can be used as a vertical • A container for chalk powder 	<ul style="list-style-type: none"> • The door is closed with a lock • Fan cooler built-in 	...
Maximum pole diameter	...	350 mm	...
External dimensions	...	280 x 260 x 210	...
Certificates	...	CE, RoHS	...
Protections	...	<ul style="list-style-type: none"> • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV • Circuit Breaker : C10, protected lines L+N • Lightning protection : <ul style="list-style-type: none"> - Maximal voltage : 385 V AC - Nominal stroke current : 20 kA (8/20µs) - Maximum stroke current : 40 kA (8/20µs) 	...
Power supply	...	100 ... 240 V AC, 50 / 60 Hz - Screw terminals	12 V DC
Operation temp	...	-20 °C ... 65 °C	-10 °C ... 55 °C
Weight	0.3 kg	5.65 kg	0.11 kg

Dimensions	120 x 75 x 44 mm	280 x 260 x 205 mm	80 x 126 x 23 mm
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00