





	<a href="#">TV OR MONITOR MOUNT ADUX160 ART</a>	<a href="#">GLUE STICKS FOR SOLDERING GUNS MCE-434 12 PCS</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-FS22-44TP</a>	<a href="#">EXTENDER RECEIVER HDMI-EX-150IR/RX-V4</a>
				
	33.21 EUR 33.21 EUR	3.83 EUR 3.83 EUR	45.62 EUR 45.62 EUR	79.57 EUR 79.57 EUR
Packaging	...	12 pcs	...	...
Device type	...	...	...	Receiver
HDMI standard	...	...	...	1.3
HDCP	...	...	...	1.4
Dimensions of the sticks	...	Ø 11 x 150 mm	...	...
Protocols	...	...	...	HDbiT
Mounting standard	VESA 200 x 200, 300 x 200, 300 x 300, 400 x 300, 400 x 400, 600 x 400	...	VESA : 100 x 100, 200 x 100, 200 x 200, 300 x 200, 300 x 300, 400 x 200 400 x 300, 400 x 400	...
Supported HDMI resolutions	...	...	...	1080p, 1080i, 720p, 576p, 576i, 480p, 480i
Screen size range	32 " ... 80 "	...	32 " ... 55 "	...
Bearing capacity	45 kg	...	35 kg	...
Distance from mounting surface	65 ... 350 mm	...	...	...
Color	Black	Transparent	Black	...
Tilt adjustment	0 ° ... 15 °	...	-10 ° ... 10 °	...
Horizontal rotation	-40 ° ... 40 °	...	—	...
Rotation in the plane of the screen	—	...	—	...
Maximal transmission range	...	...	...	<ul style="list-style-type: none"> <li>• 120 m @ 1080p - UTP cat. 6</li> <li>• 100 m @ 1080p - UTP cat. 5e</li> <li>• 80 m @ 1080p - UTP cat. 5</li> </ul>
Manufacturer / Brand	ART	...	BRATECK	...
Main features	<ul style="list-style-type: none"> <li>• A blockade to prevent the TV/monitor from slipping</li> <li>• Double arm guaranteeing stability and safety</li> <li>• Built-in bubble level for easy installation</li> <li>• In the kit : Expansion plugs, Screws</li> </ul>	<ul style="list-style-type: none"> <li>• Universal sticks for glue guns</li> <li>• A wide range of applications</li> </ul>	Adjustable shelf height in the range of 60 cm	<ul style="list-style-type: none"> <li>• IR carrier frequency : 20 ... 60 kHz</li> <li>• Baudrate : 18 Mbps</li> <li>• Protections : lightning, Overvoltage, ESD</li> </ul>
Power supply	...	...	...	5 V DC / 1 A - (power adapter included)
Current consumption	...	...	...	3 W
Operation temp	...	...	...	0 °C ... 60 °C
Weight	4.25 kg	0.014 kg (single element)	12 kg	0.146 kg
Dimensions	635 x 420 x (65 ... 350) mm	...	1170 ... 1470 x 600 x 400 mm	97 x 94 x 24 mm
Guarantee	2 years	2 years	2 years	2 years