







	AHD, HD-CVI, HD-TVI, PAL VANDAL-PROOF CAMERA DS-2CE57H0T-VP1TF(2.8mm)(C) - 5 Mpx Hikvision	CABLE PROTECTOR ATLO: KPS-13X130	MAGNET IN A HERMETIC ENCLOSURE OPXM-1 SATEL	SPEAKER CABLE HI-FI/2X0.75	REMOVABLE KEYBOARD GKX-1 FOR APT-200, MPT-300, MPT-350 REMOTE CONTROLLERS SATEL	VOICE SYNTHESIZER SM-2 SATEL
						
	130.66 CAD 130.66 CAD	8.92 CAD 8.92 CAD	13.32 CAD 13.32 CAD	0.64 CAD 0.64 CAD	4.96 CAD 4.96 CAD	37.07 CAD 37.07 CAD
Material	...	Stainless steel
Message capacity	max. 16 s
Support	AXD-200, XD-2	...	APT-200, MPT-300, MPT-350	INTEGRA, CA-64, CA-10, CA-6, GSM-4S
Main features	...	<ul style="list-style-type: none"> • 2 mounting brackets • Spring protector
Standard	AHD / HD-CVI / HD-TVI / CVBS
In section	100 m . Price for 1m when buying a whole roll
Sensor	Progressive Scan CMOS
Audio outputs	<ul style="list-style-type: none"> • LINE - telephone line listening • REPORT - recorded message listening
Matrix size	5 Mpx
Microphone	Built-in
Inner conductor	2 x Ø 0.75 mm Cu-OFC Stranded wire
Outer coating	PVC
Operation state indication	LED indicator - message recording
Coating color	Colorless
Current consumption - stanby	3 mA
Maximal current consumption	18 mA
Environment class	II
Operation temp	-10 °C ... 55 °C
Resolution	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI, • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL
Range of IR illumination	20 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm
View angle	<ul style="list-style-type: none"> • 85 ° (manufacturer data) • 79 ° (our tests result)
IR illuminator support	ICR - Movable InfraRed filter
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • D-WDR - Wide Dynamic Range Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • PLAY - recorded message listening • REC - message recording
OSD menu	✓
Power supply	12 V DC / 340 mA	9 V ... 12 V DC
Power consumption	≤ 4.3 W
Housing	Dome, Metal

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP67	...	IP65
Vandal-proof	IK10
Color	White	Silver	White
Operation temp	-40 °C ... 60 °C
Weight	0.37 kg	0.044 kg	0.05 kg	...	0.004 kg	0.035 kg
Dimensions	Ø 111 x 85 mm	<ul style="list-style-type: none"> • Ø 11 mm / 7 mm - Inner diameter, • Ø 13.5 mm / 9 mm - External diameter, • 130 mm - Length (CABLE PROTECTOR), • 50 x 20 mm - Bracket 	102 x 23 x 20 mm	...	70 x 36 x 7 mm	65 x 43 x 20 mm
Manufacturer / Brand	Hikvision	...	SATEL	...	SATEL	SATEL
SAP Code	300613629
Guarantee	3 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00