

	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE56D0T-IT3F(2.8mm)(C) - 1080p Hikvision	ACCESS POINT 4G LTE +ROUTER ARCHER-MR200 2.4 GHz, 5 GHz 433 Mbps + 300 Mbps TP-LINK
		
	61.70 EUR 61.70 EUR	84.86 EUR 84.86 EUR
Frequency range	...	2.4 GHz , 5 GHz
Standard	AHD / HD-CVI / HD-TVI / CVBS	...
Sensor	Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Resolution	1920 x 1080 - 1080p	...
Antenna type	...	3 x WiFi - built-in , 2 x 4G LTE
Range of IR illumination	40 m	...
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
Standards	...	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3/3u
View angle	<ul style="list-style-type: none"> • 106 ° (manufacturer data) • 101 ° (our tests result) 	...
IR illuminator support	ICR - Movable InfraRed filter	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Baud rates	...	<ul style="list-style-type: none"> • 5 GHz : 433 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 150 Mbps
Modulation type	...	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM

Main features	<ul style="list-style-type: none"> • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • D-WDR - Wide Dynamic Range • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Sharpness - sharper image outlines 	...
OSD menu	—	...
"Index of Protection"	IP67	...
LAN ports	...	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN
Power consumption	≤ 3 W	...
Housing	Dome, Plastic	...
Vandal-proof	—	...
Color	White	...
Operation temp	-40 °C ... 60 °C	...
SAP Code	300613493	...
Receiver sensitivity	...	5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -67dBm • 11ac HT40: -64dBm • 11ac HT80: -60dBm • 11n HT20: -71dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -76dBm • 11n HT20: -73dBm • 11n HT40: -67dBm
LTE	...	✓
QSS	...	✓
WDS	...	✓
Power supply	12 V DC / 250 mA	12 V DC / 1 A (power adapter included)
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	95 % (non-condensing)

Main features	...	<ul style="list-style-type: none"> • SIM socket • WPS/RESET button
Weight	0.21 kg	0.26 kg
Dimensions	Ø 110 x 93 mm	202 x 163 x 34 mm
Manufacturer / Brand	Hikvision	TP-LINK
Guarantee	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00