



	RELAY MODULE 4R-D7 Modbus RTU	VOLTAGE CONVERTER DCDC-11-28/12-24
		
	12.29 EUR 12.29 EUR	25.47 EUR 25.47 EUR
PTZ control	RS-485 / UART TTL	...
Type	...	Decreasing and increasing the voltage, DC/DC
Protocol	Modbus RTU	...
Power voltage	...	11 ... 28 V DC
Transmission speed	4800 / 9600 / 19200 b/s (default: 9600 b/s)	...
Number of inputs	4 pcs	...
Number of relay outputs	4 pcs	...
Relay maximal load	10 A / 250 V AC , 10 A / 30 V DC	...
Output voltage	...	<ul style="list-style-type: none"> • USB, 5 V DC, • 15 V, 16 V, 18, (18.5) V, 19 (19.5) V, 20 V, 22 V, 24 V DC - selectable by switch
Power	...	90 W
Application	...	<ul style="list-style-type: none"> • Device is dedicated to power laptops • cameras • monitors
Main features	<ul style="list-style-type: none"> • LED indication • The control inputs protected with optocouplers, which allows the use of control signals with voltages in the range of 3.3 V DC ... 30 V DC • The UART interface input is adapted to the installation of gold-pins for signals with voltages adapted to the TTL level (3.3 V DC / 5 V DC) • Possibility to configure the device address (with saving the settings after a power failure) in the range of 1 - 255 (default address 255) • Possibility to set the delay of the relay operation (base unit: 0.1 s, value range: 0.1 s ... 6553.5 s) • Protection against reverse polarity of the input voltage 	...

Output	4 x NO/NC	11 pcs 6.50/4.40mm, 2 x 5.50/2.50mm, 3.50/1.35mm, 6.30/3.00mm, 2 x 4.80/1.70mm, 5.50/3.00mm, 7.40/5.00mm, 8.0/5.50mm
Power supply	7 V ... 24 V DC (power adapter not included)	...
Weight	0.092 kg	0.25 kg
Dimensions	93 x 91 x 20 mm	112 x 51 x 30 mm
Guarantee	2 years	2 years