



| | | |
|----------------------------|---|---|
| | IP CAMERA DS-2CD2483G2-I(2.8MM) ACUSENSE - 8.3 Mpx Hikvision | TRIPOD TURNSTILE DS-K3G501SX-R/M-DM55 Hikvision |
| |  |  |
| | 268.44 EUR 268.44 EUR | 2624.23 EUR 2624.23 EUR |
| Standard | TCP/IP | ... |
| Gate passing speed | ... | ~ 35 persons/min |
| The length of the gate arm | ... | 522 mm |
| Sensor | 1/2.8 " Progressive Scan CMOS | ... |
| Passage width | ... | 550 mm |
| Matrix size | 8.3 Mpx | ... |
| RFID readers | ... | 13.56 MHz S50 |
| RS-232 | ... | x 4 |
| RS-485 | ... | x 4 |
| Resolution | 3840 x 2160 - 8.3 Mpx , 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p | ... |
| Main features | ... | <ul style="list-style-type: none"> • The gate can be operated in one or both directions • Leaving the door open after a power failure • Remote control and management • TCP/IP network communication - communication data is specially encrypted • Fire alarm mode - when triggered, the barrier will automatically lower for evacuation • 180 000 events buffer • Number of supported proximity cards : 60 000 • LED display informing about the status of the gate (entry / exit / door blockade) • Possibility of voltage control or via RS-485 interface • Housing made of stainless steel : SUS304 |
| Lens | 2.8 mm | ... |
| View angle | 108 ° | ... |

| | | |
|--|---|--------------|
| Allowable uninterrupted operation time | ... | unlimited |
| Range of IR illumination | 10 m | ... |
| Permissible relative humidity | ... | 0 % ... 95 % |
| Audio | <ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support • Compliance with the AAC standard, • Noise suppression and echo cancellation | ... |
| RS-485 interface | — | ... |
| Alarm inputs / outputs | — | ... |
| Image compression method | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Main stream frame rate | 12.5 fps @ 8.3 Mpx 25 fps @ 4 Mpx | ... |
| ONVIF | ✓ | ... |
| Network interface | 10/100 Base-T (RJ-45) | ... |
| Mobile phones support | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect | ... |
| Default IP address | DHCP or 192.168.1.64 | ... |
| Default admin user / password | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | 80 | ... |
| PC client access ports | Port no.: 8000 or access by a cloud (P2P) iVMS-4200 application | ... |
| Mobile client access ports | 8000 | ... |
| Port ONVIF | 80 | ... |
| RTSP URL | <ul style="list-style-type: none"> • Main stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization | ... |
| Memory card slot | Micro SD memory cards up to 512GB support (possible local recording) | ... |

| | | |
|----------------------|--|---------------------|
| Main features | <ul style="list-style-type: none"> • Camera from AcuSense series • Built-in PIR detector, Range : 8 m / 90 ° • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • Image rotation and mirror • Built-in Infra-Red illuminator enables night monitoring • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • Smart motion detection (with recognizing people and vehicles) • Intelligent image analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles, face detection | ... |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 490 mA | 230 V AC |
| Power consumption | <ul style="list-style-type: none"> • ≤ 6.9 W @ PoE, • ≤ 5.9 W @ 12 V DC | ... |
| Weight | 0.22 kg (with stand) | 41 kg |
| Dimensions | 76 x 135 x 82 mm (with stand) | 1208 x 960 x 728 mm |
| Operation temp | -10 ... 40 °C | -20 °C ... 65 °C |
| Supported languages | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian | ... |
| Manufacturer / Brand | Hikvision | Hikvision |
| SAP Code | 311316098 | 314608732 |
| Guarantee | 3 years | 3 years |