

	CRIMPING TOOL LY-2546B	POWER DISTRIBUTION UNIT ACARXPROTECTOR	END CLAMP PLKX40-50B FOR SOLAR PANELS 40 mm	CABLE 3C-W2C-W-1.8M 1.8 m	QUAD SMART LED LIGHTING CONTROLLER ATLO-SWA-TUYA Wi-Fi, Tuya Smart	SILVER OXIDE BATTERY BAT-377/376 ENERGIZER	ACCESS CONTROLLER MODULE MC16-PAC-ST-3 ROGER	ACCESS CONTROL PANEL ACCO-N2Z-SATEL	ROUTER ER-X EdgeMAX UBQUITI
									
	18.43 EUR 18.43 EUR	20.38 EUR 20.38 EUR	0.56 EUR 0.56 EUR	1.11 EUR 1.11 EUR	19.85 EUR 19.85 EUR	1.02 EUR 1.02 EUR	424.52 EUR 424.52 EUR	377.94 EUR 377.94 EUR	66.90 EUR 66.90 EUR
Material	Aluminum
Standards	IEEE 802.3ad, IEEE 802.1q
Material	Metal / PET
Number of served transitions	3 (two-way)
Height	40 mm
Rated voltage	...	230 V AC / 50 Hz	1.55 V
Number of channels	4
Processor	Dual-Core 880 MHz, MIPS1004Kc
Number of supported readers	12
Hole diameter	9 mm
Inputs	• 8 pcs - Mainboard inputs • max. 264
mounting screw
LAN ports	5 x LAN 10/100/1000 Mbps (RJ-45)
Number of users	unlimited (purchase of the appropriate license required)
Response time	...	< 25 ns
WAN interface	configurable
Cable	3 x CINCH Plug / 3 x CINCH Plug
Type (size)	SR626 / SR626SW / SR66 / 377 / 376
Number of outlets	...	5 grounded outlets 10A/250V
Number of media per ID
Maximal total load	...	2300 W	...	4 x 150W W
LED indicators	Power, LAN
Outputs	• 8 pcs - Mainboard inputs • max. 264
Buffer memory	8 000 000 events buffer
Total maximal current	...	10 A	...	4 x 2.5 A
DDNS	✓
Application	MC4 connector, Wire gauge : 2.5 mm ² ... 6 mm ² (AWG 13 ... AWG 10)	switching devices on/off
Number of access zones	6
Number of inputs	4
DHCP server	✓
Number of alarm zones	6
Number of outputs	4
Connector type	screw terminals
Automatic delayed fuse	...	10 A / 250 V
Leak current	...	< 0.5 mA
Wireless	• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Events memory	• Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel. • Max. 100 000 events read from each access control module
Communication	• Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface	• 2 x RS-485 • Expander bus - up to 32 expander modules	...
Radio communication range	< 100 m (open area)
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Protections	• NAT network firewall • LAN ACL • Contact/Air (ESD/EMP) : ± 24 kV / ± 24 kV
Users + admins	• 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Mobile phones support	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Nominal stroke current	...	1 kA (L/N) - (8/20µs)
Management interface	• Software EdgeOS, Software PC • Remote management • Web browser
Switch	...	two-way, with light indication
Maximum stroke current	...	4.5 kA (L/N) - (8/20µs)	• OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC
Length of the cable	...	1.45 m	...	1.8 m
Output load
"Index of Protection"	IP20
Color	Black	...	White
Power supply PoE	Ubiquiti Passive PoE

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Support for up to 255 access control modules • Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition) • Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway) • Ability to block/unblock partition at a specified time, or as per access schedule. • Ability to assign 4 identifiers and a keyfob to a single user. • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user. • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses 	<ul style="list-style-type: none"> • IEEE 802.1Q VLAN • PPPoE • Static routing • DHCP • IPv6 compliance • IGMP • NAT • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN • Dynamic DNS • Client - Radius support • QoS - mechanisms, which provide the high quality of transmission • Switch is managed via a web browser, command line interface and SNMP. • NetFlow, LLDP, NTP, UBNT Discovery Protocol protocols • View topology and network status • RESET button • Possible power supply via Passive PoE via eth4/Poe OUT port - 24 V ("+"; 4, 5 pins; "-" ; 7, 8 pins) • Possibility to mount to the wall
Battery backup support	12 V / 7 Ah	---	...
Power supply	100 ... 240 V AC, 50 / 60 Hz	...	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC / 140 mA (max)	<ul style="list-style-type: none"> • 12 V DC / 0.5 A (power adapter included) • Passive PoE 24 V - port eth0/PoE IN
Power consumption	max. 5 W
Housing	...	Plastic - non-flammable	Plastic	Metal
Operation temp	-10 °C ... 40 °C	5 °C ... 40 °C	...	-10 °C ... 55 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	...	10 % ... 90 % (non-condensing)
Weight	0.44 kg	0.51 kg	0.26 kg	0.070 kg	0.03 kg	0.001 kg	0.14 kg	0.096 kg	...	0.172 kg
Dimensions	218 x 65 x 30 mm	365 x 65 x 52 mm	50 x 43 x 30 mm	...	43 x 39 x 22 mm	Ø 6.8 x 2.6 mm	175 x 72 x 30 mm	151 x 69 x 17 mm	...	110 x 75 x 22 mm
Manufacturer / Brand	ENERGIZER	ROGER	SATEL	...	UBIQUITI
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	3 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00