






	ROUTER RG-EG310GH-REYEE	ROUTER WIFI RG-EG105GW(T) Wi-Fi 5, 867 Mbps + 400 Mbps REYEE	WHOLE HOME WI-FI SYSTEM RG-M18(2PACK) Wi-Fi 6, 2.4 GHz, 5 GHz, 547 Mbps + 1201 Mbps REYEE	ACCESS POINT +ROUTER ACB-ISP Wi-Fi 2.4 GHz 300 Mbps UBIQUITI	MULTIBAND AMPLIFIER HS-004L
					
	123619.05 HUF 123619.05 HUF	58857.14 HUF 58857.14 HUF	78857.14 HUF 78857.14 HUF	14891.43 HUF 14891.43 HUF	26805.71 HUF 26805.71 HUF
Number of devices included	2 pcs
Frequency range	...	2.4 GHz, 5 GHz	• 2.4 GHz, • 5 GHz ,	2.4 GHz	88 MHz ... 230 MHz - VHF , 470 MHz ... 790 MHz - UHF
Gain	36 dB ... 39 dB @ VHF 39 dB ... 44 dB @ UHF
Number of inputs/outputs	1 / 1 + 2 (2 x test: -30dB, -20dB)
Antenna type	...	2x2 MIMO - built-in • 3 dBi @ 2.4 GHz • 4 dBi @ 5 GHz	2x2 MU-MIMO - built-in • 4 dBi @ 2.4 GHz - 2 pcs • 6.8 dBi @ 5 GHz - 2 pcs	2x2 MIMO - built-in 4 dBi	...
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.11 a/b/g/n/ac, Wi-Fi 5	IEEE 802.11ax Wi-Fi 6	IEEE 802.11n, Wi-Fi	...
Baud rates	...	867 Mbps @ 5 GHz + 400 Mbps @ 2.4 GHz	547 Mbps @ 2.4 GHz + 1201 Mbps @ 5 GHz	300 Mbps	...
Gain adjustment	0 dB ... 20 dB @ VHF , 0 dB ... 14 dB @ UHF
LAN ports	• 6 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)	• 1 x LAN 10/100/1000 Mbps (RJ-45) • 3 x LAN/WAN 10/100/1000 Mbps (RJ-45)	2 x 10 / 100 / 1000 Mbps - RJ45	4 x 10/100 Mbps	...
Slope adjustment	14 dB @ VHF , 10 dB @ UHF
WAN interface	• 1 x WAN x 10/100/1000 Mbps (RJ-45)	• 1 x WAN x 10/100/1000 Mbps (RJ-45)	1 x 10 / 100 / 1000 Mbps - RJ45
Maximal output level IMD3=60 dB DIN45004B	121 dB _μ V
Port USB	—	✓	—
S/N ratio	< 6 dB
LED indicators	Status, Link/Act	Status, Link/Act, Mesh	Power / System / Mesh, Signal indicator
DDNS	✓	✓	—
DHCP server	✓	✓	✓
Firmware update	✓	✓	✓
Protections	• ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks	• TCP scan blocking • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping • Mechanisms to prevent the most common types of DoS (Denial-of-Service) attacks	• WPA/WPA2 • Black list • parental control • SSID hiding • Firewall	WPA2	...
Operation modes	• Repeater • Router • Access Point • WISP

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Management interface	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reeye application • Remote management • Web browser 	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reeye application • Remote management • Web browser 	<ul style="list-style-type: none"> • Configuration using the Ruijie Reeye application • Remote management • Web browser
Mobile phones support	Android: Free application Ruijie Reeye iOS (iPhone): Free application Ruijie Reeye	Android: Free application Ruijie Reeye iOS (iPhone): Free application Ruijie Reeye	Android: Free application Ruijie Reeye iOS (iPhone): Free application Ruijie Reeye
Default IP address	192.168.110.1
Transmitter power	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz	19 dBm (max)	...
Main features	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button 	<ul style="list-style-type: none"> • Support for Reeye Mesh technology • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • Reboot schedule • View topology and network status • RESET button 	<ul style="list-style-type: none"> • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • OFDMA • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Load balance • WLAN : max. 6 x BSSID • IPv4/IPv6 - Static routing • PPPoE • IPTV • WMM support (QoS mechanism of the 802.11e standard) • VPN support : PPTP VPN Server / Client • Guest Network - a separate and secure network for guests • Support for Reeye Mesh technology • System logs • RESET button • MESH button 	<ul style="list-style-type: none"> • PoE OUT 24 V - port WAN, (4, 5+; 7, 8-) • Port Security : Contact/Air (ESD/EMP) ± 24 kV / ± 24 kV • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network 	...
Housing	Plastic
Power supply PoE	—	—	—	Ubiquiti Passive PoE	...
Power supply	100 ... 240 V AC, 50 / 60 Hz	12 V DC / 1.5 A (power adapter included)	12 V DC / 1.5 A (included)	<ul style="list-style-type: none"> • 4.95 ... 5.05 V DC / 2 A - micro USB socket (power adapter not included) • PoE 24 V - Port 1 	230 V AC
Power consumption	≤ 15 W	≤ 15 W	max. 18 W	≤ 5 W	5 W
Operation temp	0 °C ... 40 °C	0 °C ... 40 °C	-10 °C ... 45 °C	-10 °C ... 50 °C	-20 °C ... 50 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	10 % ... 90 % (non-condensing)	5 % ... 95 % (non-condensing)	5 % ... 95 %	...
Weight	2.4 kg	0.29 kg	0.36 kg (single element)	0.22 kg	0.68 kg
Dimensions	440 x 207 x 44 mm	119 x 119 x 29 mm	91 x 91 x 181 mm (single element)	89 x 90 x 89 mm	179 x 135 x 52 mm
Manufacturer / Brand	RUIJIE / REYEE	RUIJIE / REYEE	RUIJIE / REYEE	UBIQUITI	...
Guarantee	2 years	2 years	3 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00