



	OVERVOLTAGE LIMITER LE-412253 THREE-PHASE 1+2 TYPE LEGRAND	IP CAMERA IPC3614LB-SF28K-G - 3.7 Mpx 2.8 mm UNIVIEW
		
	212.29 CHF 212.29 CHF	119.59 CHF 119.59 CHF
Standard	...	TCP/IP
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Device type	Overvoltage limiter, Three-phase	...
Scanning system	...	Progressive
Rated voltage	230 / 400 V AC, 50 / 60 Hz	...
Maximal voltage	320 V AC, 50 / 60 Hz	...
Class	1+2 type (Class B+C)	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
Protection level Up L/PE, N/PE	1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)	...
View angle	...	<ul style="list-style-type: none"> • 97 ° (manufacturer data) • 90 ° (our tests result)
Range of IR illumination	...	30 m
S/N ratio	...	> 52 dB
Nominal discharge current (L/PE, N/PE)	8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)	...
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Maximum stroke current (L/N, L/PE, N/PE)	50 kA @ 8/20 µs (T2)	...
Operation state indication	✓	...
Connectors type	screw terminals	...
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Width in 17.5 mm modules	4	...
Audio	...	—
Main stream frame rate	...	25 fps @ 3.7 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL / TLS, SNMP

WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Mobile phones support	...	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Sharpness - sharper image outlines
Power supply	...	• PoE (802.3af), • 12 V DC / 330 mA
Power consumption	...	≤ 4 W
Housing	Plastic, DIN, TS-35 rail mounting	Dome, Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—

Operation temp	...	-30 °C ... 60 °C
Weight	0.552 kg	0.34 kg
Dimensions	71 x 83 x 70 mm	Ø 118 x 97 mm
Supported languages	...	Polish, English
Manufacturer / Brand	LEGRAND	UNIVIEW
Guarantee	2 years	3 years