




	AHD, HD-CVI, HD-TVI CAMERA BCS- EA25FSR3(H2) - 5 Mpx 2.8 mm	SINGLE-MODE ADAPTER AD-ST/ST	MULTIPURPOSE WIRED DETECTOR XD-2L-DG SATEL
			
	45.62 EUR 45.62 EUR	0.44 EUR 0.44 EUR	32.66 EUR 32.66 EUR
Connector type	...	ST simplex	...
Support	Alarm control panel
Construction	...	single-mode	...
Housing type	...	Metal	...
Detection	Opening the door or window, Vibrations, Water
Standard	AHD / HD-CVI / HD-TVI / CVBS
Environmental class EN 50130-5	II
Protection class (Grade)	2
Sensitivity adjustment	Applies to the shock detector
Alarm signaling	LED indicator, Signal to control panel
Relay contacts rating (resistive load)	40 mA / 24 V DC
Resolution	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-CVI @ 25 fps 1920 x 1080 - 1080p - AHD, HD-TVI, HD-CVI @ 25 fps
Sensor	1/2.8 " Progressive Scan CMOS
Lens	2.8 mm, F1.2
View angle	103 °
Range of IR illumination	30 m
S/N ratio	> 50 dB
Video output	AHD / HD-CVI / HD-TVI, 1 Vpp / 75 Ω
OSD menu	✓
Audio	• Microphone built-in • Audio output

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • BLC - configurable Back Light Compensation • 3D-DNR - Digital Noise Reduction • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance
Power supply	12 V DC / 420 mA	...	12 V DC / 15 mA (max)
Power consumption	< 5 W



Main features	...	ceramic sleeve	<ul style="list-style-type: none"> • Operation modes : <ul style="list-style-type: none"> - Magnetic detector - Opening the door or window - Maximum distance between detector and magnet : 15 mm (surface magnet), 19 mm (recessed magnet) - input for connecting a NC type wired detector - 1 Alarm output <ul style="list-style-type: none"> - Shock detector - Detection of shocks and vibrations associated with attempts to force a door or window - Range : 3 m - input for connecting a NC type wired detector - 1 Alarm output <ul style="list-style-type: none"> - Shock and magnetic detector - Detection of shocks and vibrations associated with attempts to force a door or window - Opening the door or window - input for connecting a NC type wired detector - 1 / 2 Alarm outputs <ul style="list-style-type: none"> - Water flood detector - The required FPX-1 probe is available separately - detecting the presence of water in spaces where there is a risk of leakage - 1 Alarm output • Alarm output : 2EOL/NC, NC • Built-in parametric resistors 2EOL: 2 x 1.1kΩ, 2 x 2.2 kΩ, 2 x 4.7 kΩ, 2 x 5.6 kΩ, 2 x 6.8 kΩ • LED indication - Remote configuration • Supply voltage control • Tamper detection - opening the enclosure • 2 magnets included (for surface and flush mounting) • Compliance with EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-2-6 standards
---------------	-----	----------------	---



Housing	Dome, Metal
Color	White	...	Dark graphite
"Index of Protection"	IP66
Mechanical protection class	—
Operation temp	-10 °C ... 55 °C
Operation temp	-20 °C ... 60 °C
Weight	0.3 kg	...	0.04 kg (detector)
Dimensions	Ø 94 x 80 mm	...	<ul style="list-style-type: none"> • 25 x 136 x 29 mm (detector) • 15 x 52 x 6 mm (surface magnet) • Ø 10 x 28 mm (recessed magnet)
Manufacturer / Brand	BCS	...	SATEL
Guarantee	3 years	2 years	2 years