


	VIDEO SEPARATOR D-SEP2/HD	EXPANSION PLUG KW-8/4X40 KLIMAS	DUAL SMART CONTROLLER FOR ROLLER SHUTTERS ATLO-CW2-TUYA Wi-Fi, Tuya Smart
			
	6.17 EUR 6.17 EUR	0.07 EUR 0.07 EUR	18.38 EUR 18.38 EUR
Material	...	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	...
Drilling diameter	...	8 mm	...
Expansion plug length	...	40 mm	...
Maximal total load	2 x 720 W
Total maximal current	2 x 3 A
Screw dimensions	...	Ø 4 x 40 mm, PZ-2	...
Connector type	screw terminals + wires
Standard	<ul style="list-style-type: none"> AHD - 8 Mpx, 4K UHD HD-CVI - 8 Mpx, 4K UHD HD-TVI - 8 Mpx, 4K UHD CVBS - PAL / NTSC
Application	...	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	roller shutters, roof windows, awnings, drop-down screens, curtains
Device type	Passive
Manufacturer / Brand	...	KLIMAS	...
Number of inputs	1 pcs BNC socket	...	4
Number of outputs	1 pcs BNC plug	...	4
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Input impedance	75 Ω
Radio communication range	< 100 m (open area)
Output impedance	75 Ω
Opto-isolation between inputs and outputs	16 V DC
Mobile phones support	<ul style="list-style-type: none"> The Tuya Smart free application on Android The Tuya Smart free application on iOS
Attenuation	<ul style="list-style-type: none"> 4.43 MHz @ 0.21 dB 11 MHz @ 0.41 dB 21 MHz @ 0.82 dB 38 MHz @ 1.19 dB 42 MHz @ 1.17 dB 67.5 MHz @ 3.46 dB
Insertion loss	0.5 dB

Bandwidth	180 MHz
Main features	<ul style="list-style-type: none"> • Local control by physical button, • Możliwość użycia tylko przycisku monostabilnego, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control • Saving in the memory of the last adjustment of the position (from a button or application)
Power supply	—	...	100 ... 240 V AC, 50 / 60 Hz
Housing	Plastic
"Index of Protection"	IP20
Color	White
Operation temp	-20 °C ... 55 °C	...	-10 °C ... 40 °C
Weight	0.03 kg	...	0.042 kg
Dimensions	60 x 28 x 22 mm	...	<ul style="list-style-type: none"> • 43 x 39 x 22 mm • 10 cm (cable length)
Guarantee	2 years	2 years	2 years