



	<a href="#">STANDING RACK CABINET EPRADO-R19-33U/600FW</a>	<a href="#">SWITCH POE PFS3010-8ET-65 8-PORT DAHUA</a>
		
	4252.56 NOK 4252.56 NOK	701.57 NOK 701.57 NOK
Internal width	19 "	...
Internal height	33 U	...
Internal depth	520 mm (max)	...
External width	600 mm	...
External height	1672 mm	...
External depth	600 mm	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 2 x RJ45 10/100 Base-TX - Uplink,</li> <li>• 8 x RJ45 10/100 Base-TX ( 8 x PoE (802.3af/at) )</li> </ul>
Holes for fan coolers	<ul style="list-style-type: none"> <li>• 105 x 105 mm - (2 places)</li> <li>• 340 x 260 mm (total size of the hole)</li> </ul>	...
Bearing capacity	800 kg	...
Color	Black RAL9004	...
Management	...	—
Door	<ul style="list-style-type: none"> <li>• Front: glass</li> <li>• Side: metal, snap-in</li> <li>• Rear: metal, hinges</li> </ul>	...
LED diodes	...	Power, Link/Act, PoE
Transmission speed	...	10 / 100 Mbps : 2 LAN ports + 8 LAN & PoE ports
Maximal output power	...	30 W / port PoE
Maximal total power	...	65 W
MAC addresses table	...	2k
Operation modes	...	<ul style="list-style-type: none"> <li>• Extend On : 250 m, 10 Mbps</li> <li>• Extend Off : 100 m, 100 Mbps</li> </ul>

Main features	<ul style="list-style-type: none"> <li>• From the top there are 2 cable entries with dimensions 375 x 60 mm</li> <li>• The floor has 6 cable entries with dimensions of 375 x 60 mm</li> <li>• Removable side panels</li> <li>• Possibility to mount the door as left or right</li> <li>• Four rack rails for mounting devices (2x front, 2x rear)</li> <li>• 4 keys included</li> <li>• The cabinet is mounted on wheels to allow it to be moved or on 4 legs</li> </ul>	<ul style="list-style-type: none"> <li>• PoE power mode : The device supports 8-pin power supply</li> <li>• EXTEND mode - ports PoE1 ... PoE8 support transmission up to 250 m</li> <li>• Watchdog PoE / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Kensington Lock</li> </ul>
Certificates	...	CE, FCC
Power supply	...	100 V ... 240 V AC
Operation temp	...	-10 °C ... 55 °C
Weight	67.7 kg	0.77 kg
Dimensions	...	243 x 123 x 35 mm
Manufacturer / Brand	EPRADO	DAHUA
Guarantee	3 years	3 years