




	<a href="#">METAL CLEANER METAL-CLEANER/400 SPRAY</a> 400 ml AG TERMOPASTY	<a href="#">WHEEL BEARING GREASE ŁT-43 K2-LT-43/400 SPRAY</a> 400 ml K2	<a href="#">POWER SUPPLY DISTRIBUTOR LZ-1ML</a>
			
	4.05 EUR 4.05 EUR	3.88 EUR 3.88 EUR	2.94 EUR 2.94 EUR
Number of power inputs	...	...	2
Number of power outputs	...	...	6
Package	Spray 400 ml	Spray 400 ml	...
Maximal power voltage	...	...	24 V DC (typical 12V)
Maximal power supply current	...	...	• 6 A terminals • 4 A 5.5/2.1 socket
Max. output current for single output	...	...	6 A
Protection type	...	...	—
Power connectors type	...	...	Input : 5.5/2.1 socket, cable terminals Output : Cable terminals
Application	Removal of greasy dirt from metal surfaces	Lubrication : • loaded slide, ball and roller bearings, • wheel bearings, • universal joints, • tracks, • cords	...
Operation temp	...	...	-50 °C ... 55 °C
Main features	Spray formulation with a straw for easy application in hard-to-reach places	• ŁT-43 grease • Spray formulation with a straw for easy application in hard-to-reach places • Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places • It can be used in any position, even upside down	LED indicator - Input voltage
Housing type	...	...	PCB
Weight	0.35 kg	0.34 kg	0.025 kg
Dimensions	Ø 66 x 200 mm	Ø 66 x 200 mm	51 x 40 x 18 mm
Manufacturer / Brand	AG TERMOPASTY	K2	DELTA
Guarantee	...	...	3 years