

	CONNECTOR WITH ELASTIC SEALING F/6.8-OXY*P100	INSTALLATION HOLDER WM-35	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA45VR4(H2) - 5 Mpx 3.3 ... 12 mm
			
	10.17 GBP 10.17 GBP	1.32 GBP 1.32 GBP	43.89 GBP 43.89 GBP
Assembly	...	DIN rail (TS-35)	...
Number of supported devices	...	1	...
Mounting holes distance	...	37 mm	...
Standard	AHD / HD-CVI / HD-TVI / CVBS
In package	100 pcs The price for package
Connector type	"F" Straight plug
Attachment of connector elements	Twisted-on
Shield fastening	Twisting-on
Wire mounting	—
Application	Coaxial cable
Cable diameter	max. 6.8 ± 0.05 mm
Impedance	75 Ω
Material	Metal
Main features	<ul style="list-style-type: none"> • Wide frequency range • Corrosion resistance • Elastic sealing • Protective coating - oxidized
Resolution	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps 960 x 576 - 960H @ CVBS
Sensor	1/2.5 " CMOS
Lens	3.3 ... 12 mm
View angle	120 ° ... 38 °
Range of IR illumination	40 m
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	—
OSD menu	✓

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • Auto White Balance • AGC • Day/night mode • ICR - Movable InfraRed filter
Power supply	12 V DC / 670 mA
Power consumption	< 8 W
Housing	Dome, Metal
Color	White
"Index of Protection"	IP66
Mechanical protection class	—
Operation temp	-20 °C ... 60 °C
Weight	0.004 kg	0.01 kg	0.559 kg
Dimensions	11 mm x 22 mm	64 x 11 x 21 mm	Ø 119 x 98 mm
Supported languages	Polish, English
Manufacturer / Brand	BCS UNIVERSAL
Guarantee	2 years	2 years	3 years