






| | AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1200TLM-JL-A-0280B-S6-BLACK -1080p 2.8 mm DAHUA | PROMOTIONAL SET DVR + HDD NVR4208-8P-4KS2+2TB 8 CHANNELS +8- PORT SWITCH POE DAHUA | DOUBLE ROLLER BLIND SWITCH TWO-POSITION DEZ2.01/11-SIMONS54 Premium 230 V 6 A | TV OR MONITOR MOUNT BRATECK-LPA78-446 | TV OR MONITOR MOUNT BRATECK-KL22-22F |
|-------------------------------------|---|---|--|--|---|
| |  |  |  |  |  |
| | 75.84 EUR 75.84 EUR | 489.23 EUR 489.23 EUR | 46.72 EUR 46.72 EUR | 12.25 EUR 12.25 EUR | 8.87 EUR 8.87 EUR |
| Device type | ... | ... | Roller Blind Switch | ... | ... |
| Rated voltage | ... | ... | 230 V AC | ... | ... |
| Rated current | ... | ... | 6 A | ... | ... |
| Standard | AHD, HD-CVI, HD-TVI, CVBS | TCP/IP | ... | ... | ... |
| Connectors type | ... | ... | screw terminals | ... | ... |
| Supported resolutions | ... | max. 8 Mpx, 4K UHD - 3840 x 2160 px, | ... | ... | ... |
| Video outputs | ... | 1 pcs HDMI 1 pcs VGA | ... | ... | ... |
| Application | ... | ... | Flush-mounted, Simon 54 Premium product series, for Nature, Premium frames | ... | ... |
| Backlight | ... | ... | ✓ | ... | ... |
| Audio support | ... | 8 Channels - Audio from cameras | ... | ... | ... |
| Assembly | ... | ... | Claw or screw mounting | ... | ... |
| Audio inputs | ... | 1 pcs Microphone CINCH | ... | ... | ... |
| Mounting standard | ... | ... | ... | VESA : 75, 100, 100x150, 150x150, 200x100, 200, 300x200, 300, 400x200, 400x300, 400 | VESA : 50, 75, 100, 200 x 100, 200 |
| Main features | ... | ... | <ul style="list-style-type: none"> The switch allows to direct control of the roller blind motor Two-position Pictogram | ... | ... |
| Audio outputs | ... | 1 pcs CINCH | ... | ... | ... |
| Screen size range | ... | ... | ... | 37 " ... 70 " | 23 " ... 42 " |
| Resolution | 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps 960 x 576 - 960H @ PAL @ 25 fps | ... | ... | ... | ... |
| Bearing capacity | ... | ... | ... | 40 kg | 35 kg |
| Sensor | Progressive Scan CMOS | ... | ... | ... | ... |
| Image compression method | ... | H.265 / H.264 / MJPEG | ... | ... | ... |
| Lens | 2.8 mm | ... | ... | ... | ... |
| Distance from mounting surface | ... | ... | ... | 67 ... 355 mm | 19.5 mm |
| View angle | 102 ° | ... | ... | ... | ... |
| Supported hard drives | ... | 2 x 6 TB SATA | ... | ... | ... |
| Range of IR illumination | 20 m | ... | ... | ... | ... |
| Recording modes | ... | Manual, Sensor, Motion detection, Schedule | ... | ... | ... |
| White light LED illuminator range | 20 m | ... | ... | ... | ... |
| Tilt adjustment | ... | ... | ... | -15 ° ... 3 ° | — |
| IR illuminator power adjustment | Automatic | ... | ... | ... | ... |
| Horizontal rotation | ... | ... | ... | -60 ° ... 60 ° | — |
| Rotation in the plane of the screen | ... | ... | ... | -3 ° ... 3 ° | — |
| Video output | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω | ... | ... | ... | ... |
| Audio | <ul style="list-style-type: none"> Microphone built-in, Audio support via coaxial cable - HD-CVI only | ... | ... | ... | ... |
| OSD menu | ✓ | ... | ... | ... | ... |
| Network protocols | ... | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IP Filter, PPPoE, FTP, IP Search, ONVIF 2.4 | ... | ... | ... |
| External storage devices backup | ... | Backup to USB drive (pendrive, external drive) | ... | ... | ... |
| Main features | <ul style="list-style-type: none"> Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality D-WDR - Wide Dynamic Range 3D-DNR - Digital Noise Reduction BLC/HLC - Back Light / High Light Compensation ICR - Movable InfraRed filter AGC - Automatic Gain Control Privacy zones - max. 8 Auto White Balance | ... | ... | ... | ... |
| Searching and playback the records | ... | Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function All channels synchronous playback, Smart Search function | ... | ... | ... |
| Bitrate | ... | 200 Mbps (total) | ... | ... | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | | | |
|---------------------------------------|------------------|--|---|--------------------------------|---------------------|
| Housing | Dome - Metal | ... | Non-halogen plastic, PC | ... | ... |
| Network functions | ... | Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users | ... | ... | ... |
| Color | White | ... | White (RAL 9003) | Black | Black |
| "Index of Protection" | IP67 | ... | IP20 | ... | ... |
| Mechanical protection class | — | ... | ... | ... | ... |
| Operation temp | -40 °C ... 60 °C | ... | ... | ... | ... |
| Mobile phones support | ... | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application | ... | ... | ... |
| Default admin user / password | ... | admin / - The administrator password should be set at the first start | ... | ... | ... |
| Default IP address | ... | 192.168.1.108 | ... | ... | ... |
| Web browser access ports | ... | 80, 37777 | ... | ... | ... |
| Maximal total power | ... | 80 W | ... | ... | ... |
| PC client access ports | ... | 37777 | ... | ... | ... |
| Switch PoE | ... | 8-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at) | ... | ... | ... |
| Mobile client access ports | ... | 37777 | ... | ... | ... |
| Power consumption | ≤ 2.6 W | ≤ 9.6 W (without HDD) | ... | ... | ... |
| RTSP URL | ... | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream | ... | ... | ... |
| Alarm inputs / outputs | ... | 4 pcs / 2 pcs | ... | ... | ... |
| PTZ control | ... | IP Speed Dome Cameras | ... | ... | ... |
| Motion Detection | ... | 22 x 18 motion zones 6 sensitivity levels | ... | ... | ... |
| USB | ... | 1 pcs USB 2.0 1 pcs USB 3.0 | ... | ... | ... |
| Intelligent image analysis | ... | ✓ | ... | ... | ... |
| Mouse support | ... | ✓ | ... | ... | ... |
| IR remote controller in the set | ... | — | ... | ... | ... |
| Power supply | 12 V DC / 220 mA | 230 V AC | ... | ... | ... |
| Dimensions | Ø 94 x 86 mm | 375 x 328 x 53 mm | • 75 x 75 x 44 mm • 31 mm - mounting depth | 440 x 420 x (67 ... 355) mm | 265 x 222 x 19.5 mm |
| Supported languages | ... | Polish, English | ... | ... | ... |
| Country of origin | ... | China | ... | ... | ... |
| Capacity | ... | 2 TB | ... | ... | ... |
| Interface | ... | SATA 6 Gb/s | ... | ... | ... |
| Size format | ... | 3.5 " | ... | ... | ... |
| Cache memory | ... | 64 MB | ... | ... | ... |
| Designed to continuous operation 24/7 | ... | ✓ | ... | ... | ... |
| Weight | 0.31 kg | 2.55 kg 0.52 kg | 0.084 kg | 3.36 kg | 0.422 kg |
| Manufacturer / Brand | DAHUA | DAHUA Seagate | KONTAKT Simon | BRATECK | BRATECK |
| Guarantee | 3 years | 3 years 2 years | 2 years | 2 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00