

	<a href="#">BOX POSITIONER PDP/EPN</a> <a href="#">Elektro-Plast</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL</a> <a href="#">CAMERA HAC-HFW2241TU-</a> <a href="#">A-0360B-S2-DIP - 1080p 3.6 mm</a> <a href="#">DAHUA</a>	<a href="#">CONVERTER MODULE</a> <a href="#">INV/12P2000/LCD-GC Green</a> <a href="#">Cell</a>
			
	9.33 EUR 9.33 EUR	151.20 EUR 151.20 EUR	236.38 EUR 236.38 EUR
Application	Marking holes for Ø68 mm multiple boxes	...	...
Type	...	...	Increasing the voltage, DC/AC
Power voltage	...	...	12 V DC
Standard	...	AHD, HD-CVI, HD-TVI, PAL	...
Output voltage	...	...	230 V AC
Sensor	...	Progressive Scan CMOS	...
Output voltage adjustment	...	...	—
Matrix size	...	2.1 Mpx	...
Material	Plastic	...	...
Power	...	...	<ul style="list-style-type: none"> <li>• 4000 W (max),</li> <li>• 2000 W (continuous operation)</li> </ul>
Efficiency	...	...	90 % (at full load)
Length of the cables	...	...	0.6 m each
Resolution	...	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	...
Lens	...	3.6 mm	...
View angle	...	<ul style="list-style-type: none"> <li>• 86 ° (manufacturer data)</li> <li>• 83 ° (our tests result)</li> </ul>	...
Protections	...	...	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overheat</li> <li>• Discharge</li> <li>• Overvoltage</li> <li>• Reverse polarity of the input voltage</li> </ul>
Range of IR illumination	...	80 m	...
IR illuminator power adjustment	...	Automatic	...
Video output	...	AHD / HD-CVI / HD-TVI / PAL - 1 Vpp / 75 Ω	...
Audio	...	Microphone built-in - Audio support via coaxial cable - HD-CVI only	...
S/N ratio	...	> 65 dB	...
OSD menu	...	✓	...

Main features	<ul style="list-style-type: none"> <li>• Can be used in both horizontal and vertical orientation,</li> <li>• Built-in tube levels,</li> <li>• Mounting holes distance : 71 mm</li> </ul>	...	<ul style="list-style-type: none"> <li>• Color LCD : Input voltage, Output voltage, Current frequency, Work load, Battery charge level, Protections (alarm)</li> <li>• Power outputs : 2 x CEE 7/3 (Schuko), 1 x USB-A</li> <li>• Built-in USB charger in the Quick Charge 3.0 (5/9/12 V; 18W) standard</li> <li>• The converter provides sinusoidal voltage, so it can be used to power interference-sensitive devices (Pure Sine Wave)</li> </ul>
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
Power supply	...	12 V DC / 640 mA	...
Power consumption	...	≤ 7.7 W	...
Housing	...	Compact, Aluminum	...
Color	...	White	...
"Index of Protection"	...	IP67	...
Operation temp	...	-40 °C ... 60 °C	...
Weight	0.04 kg	0.73 kg	4.17 kg
Dimensions	210 x 68 x 21 mm	245 x 90 x 90 mm	347 x 210 x 93 mm
Manufacturer / Brand	Elektro-Plast Nasielsk	DAHUA	Green Cell
Guarantee	2 years	3 years	2 years