



	COAXIAL CABLE NS113-TRISHIELD/300	EXTENDER EXT-POE4 PULSAR
		
	0.38 EUR 0.38 EUR	25.79 EUR 25.79 EUR
Input voltage	...	42 ... 57 V DC
Output voltage	...	42 ... 57 V DC
In section	300 m . Price for 1m when buying a whole roll	...
Number of inputs	...	1
Number of outputs	...	2
Inner conductor	Ø 1.13 mm Cu Wire	...
Connector	...	3 x RJ-45 socket
Dielectric	Ø 4.8 mm (physical foam)	...
LED indicators	...	Link/Act
Shield	Double Al/PET	...
Braid	144 x 0.12 mm Al wire / PET	...
Outer coating	Ø 6.8 mm PVC	...
Coating color	White	...
Supported data rates	...	<ul style="list-style-type: none"> • Range : 100 m - Input, 100 m - 2 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet
Impedance	75 Ω	...
Output power	...	max. 14.4 W / port PoE , max. 20 W (total)
Protections	...	<ul style="list-style-type: none"> • Overvoltage • Overload • Short-circuit
Housing	...	Metal
Operation temp. / Relative humidity	...	-10 ... 40 °C / 10 ... 90 %
Weight	...	0.10 kg
Dimensions	...	86 x 77 x 26 mm
Manufacturer / Brand	...	PULSAR
Cable attenuation at 100m section	4.5 dB @ 50 MHz 6.0 dB @ 100 MHz 13.6 dB @ 500 MHz 17.8 dB @ 800 MHz 19.7 dB @ 1000 MHz 24.4 dB @ 1500 MHz 28.4 dB @ 2000 MHz	...
Guarantee	2 years	2 years