



	POWER DISTRIBUTION UNIT ACAR-504/WF/RACK	SMART CONTROLLER FOR ROLLER SHUTTERS SHUTTERBOX-DIN/BLEBOX Wi-Fi, 230 V AC
		
	36.62 EUR 36.62 EUR	47.14 EUR 47.14 EUR
Application	...	roller shutters, roof windows, awnings, drop-down screens, curtains
Rated voltage	230 V AC	230 V AC
Rated current	10 A (total)	...
Response time	< 25 ns	...
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Maximal total load	...	2 x 1150 W (resistance load) / 2 x 150 W (inductive or capacitive load)
Nominal stroke current	2.5 kA (L/N) - 8/20 μs	...
Total maximal current	...	2 x 5 A
Number of inputs	...	2
Maximum stroke current	6.5 kA (L/N) - 8/20 μs	...
Number of outputs	...	2
Leak current	< 0.5 mA	...
Connector type	...	screw terminals
Number of outlets	5 grounded outlets 10A/250V	...
Switch	two-way, with light indication	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Length of the cable	2.7 m	...
Mobile phones support	...	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS

Main features	...	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support • Illuminated, color front panel with an additional control button
Housing	RACK 19", 1U, Plastic - non-flammable	Plastic (ABS), DIN, TS-35 rail mounting
"Index of Protection"	...	IP20
Color	...	White
Operation temp	...	-20 °C ... 50 °C
Weight	0.59 kg	0.062 kg
Dimensions	383 x 58 x 55 mm	90 x 17.5 x 65 mm
Manufacturer / Brand	...	BleBox
Guarantee	2 years	2 years