






	HUB USB 2.0 Y-2140 80 cm	ACCESS POINT 4G LTE +ROUTER ALINK-MR920 2.4 GHz 300 Mbps	EXPANSION PLUG JPK-12X160/M5 EBOLT	EXPANSION PLUG JPK-12X200/M5 EBOLT	EXPANSION PLUG KW-8/4X60 KLIMAS
					
	19.31 PLN 19.31 PLN	201.60 PLN 201.60 PLN	6.91 PLN 6.91 PLN	7.54 PLN 7.54 PLN	0.37 PLN 0.37 PLN
Frequency range	...	2.4 GHz
Connectors	• 1 x plug - USB-A • 4 x socket - USB-A
Length of the cable	80 cm
Antenna type	...	2 x Omnidirectional antenna Wi-Fi - 8 dBi, 4G LTE
USB standard	2.0
Material	• Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized	• Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized	• Expansion plug, Polypropylene • Screw, Steel galvanized
Drilling diameter	12 mm	12 mm	8 mm
Expansion plug length	155 mm	200 mm	40 mm
Standards	...	IEEE 802.11 b/g/n, 4G LTE, 3G
Screw dimensions	Ø 8 x 160 mm, Internal thread M5	Ø 8 x 205 mm, Internal thread M5	Ø 4 x 60 mm, PZ-2
Screw	Ø 5 x 16 mm	Ø 5 x 16 mm	...
Application	for Styrofoam 100 mm	for Styrofoam 140 mm	• Concrete • Solid clay brick • Solid sand-lime brick
Baud rates	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 50 Mbps
LAN ports	...	• 1 x 10/100 Mbps - LAN/WAN • 2 x 10/100 Mbps - LAN
Receiver sensitivity	...	• 11g 54M : -74 dBm • 11n HT20 MCS7 : -71 dBm • 11n HT40 MCS7 : -67 dBm
Transmitter power	...	< 27 dBm @ 2.4 GHz
LED indicators	...	Power, WAN, WLAN, LAN, GSM
Network type	...	• 4G : FDD-LTE B1/B3/B7/B8/B20/B28 - 2100 / 1800 / 2600 / 900 / 800 / 700 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : DC- HSPA+/HSPA/UMTS B1/B8 - 2100 / 900 MHz
LTE	...	✓
QSS	...	—
WDS	...	—
DHCP server	...	✓
Protections	...	• WPA-PSK/WPA2-PSK • SSID hiding • MAC addresses filtering
Management interface	...	Web browser

Main features	...	<ul style="list-style-type: none"> • SIM socket • ON/OFF button • WPS/RESET button • DHCP client/server support • DHCP client list • Static routing • Default address : 192.168.1.1 • WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems
Power supply	...	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 5 V / 2 A via micro USB port
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	0.03 kg	0.32 kg
Dimensions	65 x 23 x 19 mm	200 x 145 x 49 mm
Manufacturer / Brand	UNITEK	ALINK	EBOLT	EBOLT	KLIMAS
Guarantee	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00