



| | | |
|-----------------------|---|---|
| | WIRED DOORBELL OR-DP-VD-145/W/8V ORNO | ACCESS POINT +ROUTER ARCHER-VR400 VDSL / ADSL 300 Mbps + 867 Mbps |
| |  |  |
| | 10.57 EUR 10.57 EUR | 80.83 EUR 80.83 EUR |
| Signaling mode | Sound signaling | ... |
| Frequency range | ... | <ul style="list-style-type: none"> • 2.4 GHz, • 5 GHz |
| Number of ring-tones | 1 - Two alternating ring tones | ... |
| Volume adjustment | — | ... |
| Color | White | ... |
| "Index of Protection" | IP20 | ... |
| Standards | ... | IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5 |
| LAN ports | ... | 3x RJ-45 (10/100 Mbps, Auto MDI/MDX) 1x RJ-45 (10/100/1000 Mbps, Auto MDI/MDX) |
| WAN interface | ... | 1x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 |
| Transmitter power | ... | < 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz |
| Baud rates | ... | 300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz |
| DHCP server | ... | ✓ |
| Firmware update | ... | ✓ |
| DDNS | ... | ✓ |

| | | |
|-------------------------------|--------------------------------------|---|
| Protections | ... | <ul style="list-style-type: none"> • LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL • WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES |
| Management interface | ... | Web browser |
| Main features | Simple and quick device installation | <ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • 1 x Port USB 2.0 • The DSL line splitter included |
| Operation temp | ... | 0 °C ... 40 °C |
| Permissible relative humidity | ... | max. 90 % (max) |
| Power supply | 8 V AC | 12 V DC / 1.5 A (power adapter included) |
| Weight | 0.11 kg | 0.32 kg |
| Dimensions | 92 x 92 x 40 mm | 216 x 125 x 32 mm |
| Manufacturer / Brand | ORNO | TP-LINK |
| Guarantee | 2 years | 2 years |