





	HUB USB 3.0 F7U-U3-CR-BP 1 m	ACCESS CONTROLLER MODULE MC16-PAC-EX-10 ROGER	TV OR MONITOR MOUNT BRATECK-FS22-44TP	EXPANSION PLUG KW-8/4X40 KLIMAS
				
	348.78 CZK 348.78 CZK	47468.73 CZK 47468.73 CZK	1120.01 CZK 1120.01 CZK	1.73 CZK 1.73 CZK
Number of served transitions	...	10
Inputs	...	60
Outputs	...	40
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized
Drilling diameter	8 mm
Number of users	...	max. 12000 - Number of identifiers
Expansion plug length	40 mm
Connectors	<ul style="list-style-type: none"> 1 x Socket - micro USB 3.0 7 x socket - USB-A 1 x Power socket - micro USB
Length of the cable	1 m
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
USB standard	3.0
Number of permissions per ID	...	100
Screw dimensions	Ø 4 x 40 mm, PZ-2
Mounting standard	VESA : 100 x 100, 200 x 100, 200 x 200, 300 x 200, 300 x 300, 400 x 200, 400 x 300, 400 x 400	...
Buffer memory	...	8 000 000 events buffer
MCT readers support	...	16 pcs
Screen size range	32 " ... 55 "	...
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick
Bearing capacity	35 kg	...
Readers connections	...	4 pcs - Wiegand / PRT
Number of login points	...	20
Color	Black	...
Number of access terminals	...	40
Number of access zones	...	20
Tilt adjustment	-10 ° ... 10 °	...
Number of alarm zones	...	20
Horizontal rotation	—	...
Number of automation nodes	...	20

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Rotation in the plane of the screen	—	...
Battery backup support	...	12 V / 7 Ah
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)
Main features	<ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the micro USB socket • LED indication • Transparent housing 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	Adjustable shelf height in the range of 60 cm	...
Power supply	5 V DC / 3 A (power adapter not included)	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	...	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Weight	0.050 kg	0.14 kg	12 kg	...
Dimensions	135 x 35 x 19 mm	175 x 72 x 30 mm	1170 ... 1470 x 600 x 400 mm	...
Manufacturer / Brand	ORICO	ROGER	BRATECK	KLIMAS
Guarantee	2 years	3 years	2 years	2 years

