






	4-CHANNEL REMOTE CONTROL UREMOTE-PRO/BLEBOX Wi-Fi	POWER DISTRIBUTION UNIT ACAR-F5/FA/RACK	MULTI-SOCKET PLUG LE-49400 3680 W LEGRAND	ANGULAR PLUG LE-50461 230 V 16 A LEGRAND	ACCESS CONTROLLER ASC3202B DAHUA
					
	28.09 GBP 28.09 GBP	23.04 GBP 23.04 GBP	4.91 GBP 4.91 GBP	9.18 GBP 9.18 GBP	425.31 GBP 425.31 GBP
Number of served transitions	2
Rated voltage	...	230 V AC / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	...
Support	Cooperation with the access control systems
Maximal current load	16 A	...
Nominal load current	...	max. 10 A (total)
Maximal total load	...	2300 W	3680 W	3500 W	...
Number of supported readers	• 2 pcs RS-485, • 2 pcs Wiegand
Battery backup support	—
Electrical cable	max. 3 x 1.5 mm ²	...
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Total maximal current	16 A (6 A socket)
Alarm inputs / outputs	2 / 2
Cable terminals	screw terminals	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Number of outlets	...	5 grounded outlets 10A/250V	4 pcs
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Socket type	2P (flat)	CEE 7/5	...
Automatic delayed fuse	...	10 A / 250 V
Operation range	≤ 100 m (in open area) ≤ 40 m (internal)
Plug type	CEE 7/4 (Schuko)	CEE 7/7	...
Nominal stroke current	...	2 kA (L/N) - 8/20 μs
Grounding	—	✓	...
Mobile phones support	• The wBox free application on Android • The wBox free application on iOS
Maximum stroke current	...	10 kA (L/N) - 8/20 μs 2 type
Communication	• 3 x RS-485, • 2 x Wiegand 34/26, • 1 x Ethernet 10 / 100 Mbps (RJ-45)
Response time	...	< 25 ns
Switch	...	two-way, with light indication
Network protocols	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI
Operation modes	• Main control mode • Sub control mode
Length of the cable	...	2.9 m

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Number of buttons : 4 • 4 independent channels, • 4 groups, • Number of supported devices : 3 / Channel, • Controlling BleBox devices • Order confirmation • LED indication • Built-in vibration function (haptic feedback), • Bidirectional communication • Transmission encryption • µWiFi technology support • Control possible without Wi-Fi network available 	<ul style="list-style-type: none"> • Current paths shutters • DC filter to eliminate interferences : ≤ 35 dB 	...	Plug equipped with an additional socket outlet, compliant with the Uni-Schuko standard	<ul style="list-style-type: none"> • Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control) • 1000 indexed users • Support up to 3000 finger prints • Memory of 5000 RFID cards • Support storage of 300 000 records • 128 General Purpose Schedules • Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above • Tamper protections • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Beep signal - Buzzer • White list, Black list • Web-Server built-in • Software update via network • Monitoring and configuration through network - SmartPSS Lite application • Power output 12 V DC / 1 A - supplying power to the lock • Support hardware I/O port configuration and export configuration diagrams • ONVIF compliance
Power supply	<ul style="list-style-type: none"> • built-in battery - lithium-polymer • 5 V micro USB (battery charging) • Estimated battery operation time : 2 years 	<ul style="list-style-type: none"> • 12 V DC / 2.5 A • PoE (802.3at)
Power consumption	<ul style="list-style-type: none"> • ≤ 2 W (standby) • max. 20.4 W @ 12 V (operation) • max. 14.4 W @ PoE (operation)
Housing	Metal + Plastic (ABS)	RACK 19", 1U, Plastic - non-flammable	Plastic	...	Plastic (PC + ABS)
Color	White	...	White / Light gray	White / Gray	White
IK rating	IK06
Operation temp	-20 ... 50 °C	-10 °C ... 55 °C
Permissible relative humidity	5 % ... 95 % (non-condensing)
Weight	0.058 kg	0.93 kg	0.104 kg	0.07 kg	0.72 kg
Dimensions	72 x 39 x 12 mm	484 x 54 x 55 mm	96 x 74 x 72 mm	79 x 75 x 55 mm	186 x 186 x 58 mm
Manufacturer / Brand	BleBox	...	LEGRAND	LEGRAND	DAHUA
Guarantee	2 years	2 years	2 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00