





	TV OR MONITOR MOUNT BRATECK-LPA39-223	CABLE RJ11-W/RJ11-W/2M 2 m	EXPANSION PLUG KS-12/8X100 KLIMAS	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI- H83C61-2812W - 8.3 Mpx, 4K UHD 2.8 ... 12 mm
				
	174.45 NOK 174.45 NOK	4.59 NOK 4.59 NOK	4.70 NOK 4.70 NOK	902.32 NOK 902.32 NOK
Cable	...	RJ 11 Plug / RJ 11 Plug
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	...
Standard	AHD, HD-CVI, HD-TVI, CVBS
Drilling diameter	12 mm	...
Mounting standard	VESA 75, 100, 200x100, 200
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Length of the cable	...	2 m
Expansion plug length	80 mm	...
Matrix size	8.3 Mpx
Main features	...	<ul style="list-style-type: none"> Very easy and quick assembly
Screen size range	23 " ... 42 "
Bearing capacity	35 kg
Screw dimensions	Ø 8 x 100 mm, SW-13	...
Distance from mounting surface	45 ... 508 mm
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	...
Tilt adjustment	-15 ° ... 10 °
Horizontal rotation	-90 ° ... 90 °
Rotation in the plane of the screen	± 3 °
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD / HD-CVI / HD-TVI, 15 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps / 12.5 fps , 2592 x 1944 - 5 Mpx @ HD-CVI, 20 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI, 25 fps / 30 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI, 25 fps / 30 fps , 960 x 576 - 960H @ CVBS
Range of IR illumination	60 m

IR illuminator power adjustment	Automatic
Lens	2.8 ... 12 mm
View angle	<ul style="list-style-type: none"> • 87 ° ... 24 ° (manufacturer data) • 84 ° ... 33 ° (our tests result)
S/N ratio	> 50 dB
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / CVBS - Via OSD, selectable by switch
Main features	<ul style="list-style-type: none"> • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines
OSD menu	✓
Power supply	12 V DC / 590 mA
Power consumption	≤ 7.1 W
Housing	Compact - Metal
Color	Black	Black	...	White
"Index of Protection"	IP67
Operation temp	-20 °C ... 50 °C
Weight	2.7 kg	0.030 kg	...	0.66 kg
Dimensions	226 x 229 x (45 ... 508) mm	211 x 90 x 90 mm
Supported languages	English, Spanish, Portuguese
Manufacturer / Brand	KLIMAS	APTI
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00