



	ACCESS CONTROLLER MODULE MC16-PAC-EX-1 ROGER	ACCESS CONTROLLER ASC2202B-D DAHUA
		
	334.50 EUR 334.50 EUR	264.97 EUR 264.97 EUR
Number of served transitions	1	2 (two-way)
Support	...	DAHUA
Inputs	8	...
Number of supported readers	...	4 pcs
Outputs	8	...
Number of users	max. 12000 - Number of identifiers	...
Output lines	...	4 pcs - Relay
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Number of permissions per ID	100	...
Buffer memory	8 000 000 events buffer	...
MCT readers support	16 pcs	...
Readers connections	4 pcs - Wiegand / PRT	...
Number of login points	2	...
Number of access terminals	4	...
Number of access zones	2	...
Number of alarm zones	2	...
Number of automation nodes	2	...
Battery backup support	12 V / 7 Ah	—
Default IP address	...	192.168.0.2
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger) 	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand
Default admin user / password	...	admin / - The administrator password should be set at the first start

Main features	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems) 	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 1.4 A
Operation temp	5 °C ... 40 °C	-30 °C ... 60 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	max. 95 % (non-condensing)
Weight	0.14 kg	0.4 kg
Dimensions	175 x 72 x 30 mm	210 x 106 x 50 mm
Manufacturer / Brand	ROGER	DAHUA
Guarantee	3 years	3 years