



|                                   |  |   |
|-----------------------------------|--|---|
|                                   | <a href="#">IP CAMERA APTI-502V2L-28WP Full-Color - 5 Mpx 2.8 mm</a>   | <a href="#">DOUBLE SURFACE SOCKET OUTLET ATLO-S2IP6 IP66</a>                        |
|                                   |   |  |
|                                   | 101.82 EUR<br>101.82 EUR   | 11.99 EUR<br>11.99 EUR  |
| Standard                          | TCP/IP   | ...   |
| Sensor                            | 1/2.8 " SONY Starvis™ Back-illuminated CMOS  | ...   |
| Matrix size                       | 5 Mpx  | ...   |
| Rated voltage                     | ...  | 220 ... 240 V, 50 / 60 Hz   |
| Maximal total load                | ...  | 3840 W  |
| Total maximal current             | ...  | 16 A  |
| Number of outlets                 | ...  | 2 pcs   |
| Socket type                       | ...  | CEE 7/3 (Schuko)  |
| Grounding                         | ...  | ✓   |
| Main features                     | ...  | Current paths shutters  |
| Resolution                        | 2592 x 1944 - 5 Mpx ,<br>2560 x 1440 - 3.7 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 720 - 720p   | ...   |
| Lens                              | 2.8 mm   | ...   |
| Operation temp                    | ...  | -20 °C ... 60 °C  |
| View angle                        | 93 °   | ...   |
| White light LED illuminator range | 25 m   | ...   |
| Image compression method          | H.265+ / H.265 / H.264+ / H.264 / MJPEG  | ...   |
| Main stream frame rate            | 25 fps @ 5 Mpx   | ...   |
| Memory card slot                  | —  | ...   |
| Alarm inputs / outputs            | —  | ...   |
| Network interface                 | 10/100 Base-T (RJ-45)  | ...   |
| Audio                             | • Microphone built-in<br>• Audio transmission via network  | ...   |
| WEB Server                        | Built-in   | ...   |
| Max. number of on-line users      | 10   | ...   |
| ONVIF                             | 19.12  | ...   |
| RS-485 interface                  | —  | ...   |
| Mobile phones support             | Port no.: 80 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BitVision</a><br>• iOS (iPhone): Free application <a href="#">BitVision</a> | ...   |

|                               |   |         |
|-------------------------------|---|---------|
| Default IP address            | 192.168.1.168   | ...     |
| Default admin user / password | admin / admin<br>The administrator password should be set at the first start  | ...     |
| Web browser access ports      | 80  | ...     |
| PC client access ports        | 80  | ...     |
| Mobile client access ports    | 80  | ...     |
| Port ONVIF                    | 80  | ...     |
| RTSP URL                      | rtsp://user:password@ip_address:80/0<br>- Main stream<br>rtsp://user:password@ip_address:80/1<br>- Sub stream   | ...     |
| Main features                 | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• ICR - Movable InfraRed filter</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), loitering detection, motion detection based on human detection, detection of people gathering, vehicle detection, video tampering</li> </ul> | ...     |
| Power supply                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 400 mA</li> </ul>  | ...     |
| Power consumption             | ≤ 4.8 W   | ...     |
| Housing                       | Dome - Metal + Plastic  | Plastic |
| Color                         | White   | Gray    |
| "Index of Protection"         | IP67  | IP66    |
| Vandal-proof                  | —   | ...     |
| Operation temp                | -20 °C ... 60 °C  | ...     |

|                      |  |                    |
|----------------------|--|--------------------|
| Weight               | 0.59 kg  | 0.625 kg           |
| Dimensions           | Ø 127 x 102 mm   | 165 x 171 x 113 mm |
| Supported languages  | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Ukrainian, Italian | ...                |
| Manufacturer / Brand | APTI   | ATLO               |
| Guarantee            | 2 years  | 2 years            |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00