



	REAR SUPPORT FOR THE MOUNTING PROFILE USP-TN-600 FOR SOLAR PANELS	POE SWITCH WITH BUFFERED POWER SUPPLY IPUPS-8-20-H 8-PORT ATTE
		
	5.47 GBP 5.47 GBP	285.20 GBP 285.20 GBP
Material	Aluminum	...
LAN ports	...	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-T - Uplink, • 8 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE
Management	...	—
LED diodes	...	AC, DC, CHARGING (battery charging), PoE, Gigabit Ethernet
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port Uplink, • 10 / 100 Mbps : 8 x Port LAN & PoE
Maximal output power	...	<ul style="list-style-type: none"> • 40 W @ Passive PoE - LAN1 ... LAN8 ports, • 30 W @ PoE (802.3af/at) - LAN1 ... LAN8 ports
Maximal total power	...	60 W
Operation modes	...	Standard : 100 m @ 10/100 Mb/s - LAN1 ... LAN8 ports

Main features	...	<ul style="list-style-type: none"> • 4K UHD support • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • 2 x Place for battery : 12 V / 18 Ah • Place for recorder (NVR) • Battery charging current : 1 A / 2 A - (set with the JP1 jumper) • Battery - Protection against reverse polarity connection, Protection against deep discharge of the battery • Technical outputs of the OC type signaling loss of voltage at the PSU output (OUF) and loss of voltage in the 230V mains (ACF) • PSU thermal protection : 130 °C • Overload protection • LAN & PoE ports - Short-circuit protection, Overvoltage • TAMPER switch indicating open the cover • "Index of Protection" : IP20
Power supply	...	190 ... 260 V AC
Weight	0.32 kg	4.40 kg
Dimensions	600 x 35 x 35 mm	455 x 405 x 150 mm
Manufacturer / Brand	...	ATTE
Guarantee	2 years	3 years