



	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-B2A21-0360B - 1080p 3.6 mm DAHUA	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps
		
	52.11 EUR 52.11 EUR	108.06 EUR 108.06 EUR
Standard	AHD, HD-CVI, HD-TVI, PAL	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	...
Lens	3.6 mm	...
Frequency range	...	<ul style="list-style-type: none"> • Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz
View angle	<ul style="list-style-type: none"> • 93 ° (manufacturer data) • 90 ° (our tests result) 	...
Range of IR illumination	20 m	...
IR illuminator power adjustment	Automatic	...
Antenna type	...	<ul style="list-style-type: none"> • 4 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Integrated
Standards	...	IEEE 802.11 b/g/n/ac
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	...
OSD menu	OSD menu available via DAHUA recorder	...
Baud rates	...	<ul style="list-style-type: none"> • Wi-Fi : 866 Mbps + 300 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Auto White Balance 	...
LAN ports	...	1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN
Power consumption	≤ 2.7 W	...
Housing	Compact, Aluminum	...
Color	White	...
LED indicators	...	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN
"Index of Protection"	IP67	...
SIM socket	...	1 x mini SIM
Operation temp	-40 °C ... 60 °C	...
DDNS	...	✓
DHCP server	...	✓
Firmware update	...	✓
Manufacturer / Brand	DAHUA	...
Protections	...	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Management interface	...	Web browser
Transmitter power	...	< 20 dBm
Main features	...	<ul style="list-style-type: none"> • Built-in 5-port switch • RESET button • Remote management
Power supply	12 V DC / 220 mA	12 V DC / 1 A (power adapter included)
Weight	0.25 kg	0.42 kg
Dimensions	158 x 70 x 70 mm	238 x 149 x 33 mm
Guarantee	3 years	2 years