



	<a href="#">COAXIAL CABLE RF-7 50 Ω</a>	<a href="#">POWER SUPPLY DISTRIBUTOR LZ-12C/R19</a>
		
	1.97 EUR 1.97 EUR	37.55 EUR 37.55 EUR
Number of power outputs	...	12 (2 x 6 outputs)
Number of power inputs	...	2 (one per each 6-outputs terminal)
Maximal power voltage	...	24 V DC (typical 12V)
In section	<b>100 m . Price for 1m when buying a whole roll</b>	...
Maximal power supply current	...	5 A (for single terminal)
Max. output current for single output	...	1 A
Inner conductor	Ø 1.85 mm Cu ± 0.05 mm - Cu stranded wire	...
Protection type	...	12 x 1 A 5/20mm delayed fuse
Dielectric	Ø 5 mm - Physical foam	...
Shield	Double-sided foil - Cu/PET/Cu	...
Braid	80 % Cu	...
Power connectors type	...	Input : Cable terminals Output : Cable terminals
Impedance	50 Ω	...
Operation temp	...	-50 °C ... 55 °C
Permissible relative humidity	...	< 95 %
Outer coating	Ø 7.3 mm ± 0.2 mm PE - Black	...
Housing type	...	RACK 19", 1U
Weight	...	0.34 kg
Dimensions	...	482 x 45 x 64 mm
Main features	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• it can be used in WLAN 2,4GHz and 5GHz installations</li> <li>• Operation temp : -30 °C ... 70 °C</li> </ul>	...

Cable attenuation at 100m section	2 dB @ 10 MHz 6.4 dB @ 100 MHz 9.1 dB @ 200 MHz 14.1 dB @ 500 MHz 20.9 dB @ 800 MHz 25.9 dB @ 1 GHz 31 dB @ 1.5 GHz 35 dB @ 2 GHz 39 dB @ 2.5 GHz	...
Maximum transmitted power	3.27 kW @ 10 MHz 1.025 kW @ 100 MHz 0.693 kW @ 200 MHz 0.452 kW @ 500 MHz 0.310 kW @ 800 MHz 0.253 kW @ 1 GHz 0.219 kW @ 1.5 GHz 0.195 kW @ 2 GHz 0.175 kW @ 2.5 GHz	...
Manufacturer / Brand	...	DELTA
Guarantee	2 years	3 years