




	NVR NVR301-08X 8 CHANNELS UNIVIEW	RFID PROXIMITY CARD ATLO-307 13.56 MHz S50	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T-ITMFS(2.8MM) - 5 Mpx Hikvision
			
	219.00 EUR 219.00 EUR	0.48 EUR 0.48 EUR	70.79 EUR 70.79 EUR
Standard	...	13.56 MHz S50	...
Compatibility	...	ISO/IEC 14443A	...
Possibility of programming the serial number (ID)	...	—	...
Supported resolutions	max. 8.3 Mpx 4K UHD - 3840 x 2160 px
Ability to write to internal memory	...	1 kB	...
Standard	TCP/IP	...	AHD / HD-CVI / HD-TVI / CVBS
Video outputs	1 pcs HDMI 4K 1 pcs VGA
Serial Number overprint	...	—	...
Sensor	Progressive Scan CMOS
Matrix size	5 Mpx
Audio support	8 Channels - Audio from cameras
Audio inputs	1 pcs CINCH
Audio outputs	1 pcs CINCH
Main features	...	Range : ~ 10 cm ,	...
Image compression method	Ultra 265 / H.265 / H.264
Supported hard drives	1 x 8 TB SATA
Recording modes	Manual, Motion Detection, Schedule
Resolution	<ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL
Range of IR illumination	30 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm

Network protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, ONVIF
View angle	<ul style="list-style-type: none"> • 86 ° (manufacturer data) • 90 ° (our tests result)
External storage devices backup	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Records playback from max. 8 channels in the same time 1/4/6/8/9 channel synchronous playback
Bitrate	max. 64 Mbps
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio support via coaxial cable - HD-TVI only
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users Cloud update
ONVIF	✓
Default admin user / password	admin / 123456
Default IP address	DHCP or 192.168.1.30
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
Web browser access ports	80, 554
OSD menu	OSD menu available via recorder
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Power consumption	≤ 3.7 W
Housing	Dome, Metal

Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Color	White
Alarm inputs / outputs	—
"Index of Protection"	IP67
PTZ control	PTZ Uniview cameras
Vandal-proof	—
Motion Detection	✓
Intelligent image analysis	✓
Operation temp	-40 °C ... 60 °C
USB	• 1 x USB 2.0 • 1 x USB 3.0
Mouse support	✓
IR remote controller in the set	—
SAP Code	300613330
Main features	<p>Functions implemented in cooperation between the recorder and cameras that support these functions</p> <ul style="list-style-type: none"> • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Motion Detection • Audio detection • IVS analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing, abandoned/missing object, face detection, counting people in a given area 	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
Power supply	12 V DC / 2 A (power adapter included)	...	12 V DC / 310 mA
Weight	0.90 kg	0.005 kg	0.29 kg
Dimensions	260 x 247 x 47 mm	86 x 54 x 0.8 mm	90 x 83 x 79 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Country of origin	China
Manufacturer / Brand	UNIVIEW	ATLO	Hikvision
Guarantee	3 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00