



	<a href="#">IP VANDALPROOF CAMERA DS-2CD4525FWD-IZH(8-32MM) - 1080p Hikvision</a>	<a href="#">SWITCH POE IP-5-11-M2 5-PORT ATTE</a>
		
	7352.52 DKK 7352.52 DKK	859.57 DKK 859.57 DKK
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
LAN ports	...	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>
Resolution	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Management	...	—
LED diodes	...	Power, LAN
Transmission speed	...	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Maximal output power	...	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>
Maximal total power	...	96 W
Lens	8 ... 32 mm - Motozoom	...
View angle	<ul style="list-style-type: none"> <li>• 31 ° ... 10.2 ° (manufacturer data)</li> <li>• 30 ° ... 9.8 ° (our tests result)</li> </ul>	...
Range of IR illumination	50 m	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	...
Image compression method	H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...
Operation modes	...	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> <li>• Port LAN 6 - Uplink</li> </ul>
Audio	<ul style="list-style-type: none"> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> </ul>	...

Main features	...	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• The ABOX-M2 mounting enclosure is equipped with 7 cable entries with glands in the 6 x M16 + 1 x M20 arrangement</li> </ul>
Bitrate	32 kbps ... 16384 kbps @ H.264	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, Bonjour	...
WEB Server	Built-in, Web Viewer	...
Max. number of on-line users	20	...
ONVIF	2.4	...
Main stream frame rate	50 fps @ 1080p	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> <li>• iOS (iPhone): Free application <a href="#">iVMS-4500</a> or <a href="#">Hik-Connect</a></li> </ul>	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.64	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...

RTSP URL	<ul style="list-style-type: none"> <li>• Main stream rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>• Sub stream rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Motozoom lens</li> <li>• ICR - Movable InfraRed filter</li> <li>• WDR - 140 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• IP addresses filtering</li> <li>• WB - White Balance (ATW/AWB/manual/indoor/outdoor)</li> <li>• BLC - configurable Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Motion Detection</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, abandoned/missing object, scene changing, face detection, people counting, heat map</li> <li>• Configurable Privacy Zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• RESET button</li> <li>• The device has a built-in heater</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3at),</li> <li>• 12 V DC / 1.4 A,</li> <li>• 24 V AC / 1 A</li> </ul>	230 V AC - cable terminals
Power consumption	≤ 17 W	...
Housing	Dome - Metal	...
Color	White	...
Vandal-proof	IK10	...
"Index of Protection"	IP66	...
Operation temp	-30 °C ... 60 °C	...
Weight	1.38 kg	0.65 kg
Dimensions	Ø 165 x 127 mm	226 x 148 x 80 mm
Supported languages	Polish, English, Bulgarian, Chinese, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Japanese, Korean, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	...
Manufacturer / Brand	Hikvision	ATTE
SAP Code	300805150	...
Guarantee	3 years	3 years