



	<a href="#">IP VANDALPROOF CAMERA IPC-HDBW3441F-AS-M-0280B - 4 Mpx 2.8 mm DAHUA</a>	<a href="#">ACCESS CONTROLLER ASC2204B-S DAHUA</a>
		
	191.91 EUR 191.91 EUR	286.17 EUR 286.17 EUR
Number of served transitions	...	4 (one-way)
Standard	TCP/IP	...
Support	...	DAHUA
Sensor	1/3 " Progressive Scan CMOS	...
Number of supported readers	...	4 pcs
Matrix size	4 Mpx	...
Battery backup support	...	—
Scanning system	Progressive	...
Output lines	...	5 pcs - Relay
Communication	...	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand</li> </ul>
Resolution	2688 x 1520 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Lens	2.8 mm	...
Main features	...	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 150000 events</li> <li>• Remote programming from PC</li> <li>• Function of protection against multiple use of the same card for access (anti-passback)</li> <li>• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value</li> <li>• Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress</li> </ul>
View angle	<ul style="list-style-type: none"> <li>• 103 ° (manufacturer data)</li> <li>• 96 ° (our tests result)</li> </ul>	...
Range of IR illumination	50 m	...
RS-485 interface	—	...
Operation temp	...	-30 °C ... 60 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Permissible relative humidity	...	max. 95 % (non-condensing)
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio detection</li> </ul>	...
Bitrate	3 ... 8192 kbps	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4, IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, IEEE 802.1x, SNMP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	18.06	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> <li>• ICR - Movable InfraRed filter</li> <li>• Mirror - Mirror image</li> <li>• IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles</li> </ul>	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>	...
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.108	192.168.0.2
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...



Power supply	<ul style="list-style-type: none"> <li>PoE (802.3af),</li> <li>12 V DC / 470 mA</li> </ul>	12 V DC / 1.4 A
Power consumption	≤ 5.7 W	...
Housing	Dome, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	IK10	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.38 kg	0.354 kg
Dimensions	Ø 109 x 55 mm	207 x 116 x 52 mm
Supported languages	Polish, English, Arabic, Czech, French, Spanish, Dutch, Korean, German, Persian, Portuguese, Russian, Italian	...
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00