



	OBJECT PROTECTION SYSTEM-MANAGEMENT SERVER DSS7016LSZ DAFUA	COAXIAL CABLE TRISET- B2CA500 A++
		
	16434.78 EUR 16434.78 EUR	0.83 EUR 0.83 EUR
Standard	TCP/IP	..
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	..
In section	..	500 m . Price for 1m when buying a whole roll
Number of video channels	max. 2000	..
Coaxial cable	..	TRISSET
Video outputs	• 3 pcs HDMI • 1 pcs VGA	..
Inner conductor	..	Ø 1.05 mm Cu Wire
Audio inputs	1 pcs Microphone - Jack 3.5 mm socket	..
Dielectric	..	Ø 4.6 mm (physical foam)
Audio outputs	1 pcs - Jack 3.5 mm socket	..
Shield	..	Triple • Foil - AU/PET/SY • Foil - AU/PET Screening efficiency class A++
Braid	..	82 % - Cu + Sn wire
Supported hard drives	• 15 x 10 TB SATA III • Cooperation with the DAFUA disk arrays of the ESS series Maximum supported total disk space : 200 TB Possibility of operation the disks in RAID 0/1/5/6/10 array	..
Outer coating	..	Ø 6.9 mm PVC LSZH
Coating color	..	White
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function	..
Minimal bend radius	..	35 mm
Network interface	4 x 10/100/1000 Base-T	..
Impedance	..	75 Ω
Bitrate	max. 700 Mbps	..
Capacity	..	52 pF/m
Resistance of the inner conductor for DC current	..	20 Ω/km
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 200 on-line users	..
Screening efficiency	..	> 105 dB @30 ... 1000 MHz > 95 dB @1 ... 2 GHz > 85 dB @2 ... 3 GHz
Mobile phones support	✓	..
Shortening wave coefficient	..	85 %
Default IP address	192.168.1.108	..
Default admin user / password	admin / - The administrator password should be set at the first start	..
Web browser access ports	80, 37777	..
PC client access ports	37777	..
Main features	..	• low attenuation • perfect matched • high screening efficiency • The cable complies with the EN50117 standard and A++ class requirements in the whole transmission frequency range • Reaction to fire class in accordance with CPR - B2ca-s1a, s1a1
Alarm inputs / outputs	4 / 2	..
PTZ control	IP Speed Dome Cameras, RS-485	..
RS-485	✓	..
RS-232	✓	..
Motion Detection	✓	..
Intelligent image analysis	✓	..
Mouse support	✓	..
ANVR	max. 64 cameras	..
Face recognition	max. 64 cameras	..


DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

<p>Main features</p>	<ul style="list-style-type: none"> • Cooperation with DAHUA recorders • IP Dahua cameras support • Cooperation with POS (Point of Sale) terminals - max. 64 devices • Cooperation with the DAHUA access control systems - support max. 256 doors • Cooperation with the DAHUA IP video doorphone systems : <ul style="list-style-type: none"> - Voice calls between the VTH series internal panels and the system management center - Video calls between door stations of the VTO series and the system management center - Work as a SIP server - Group connection with the VTH internal panels and devices compliant with the SIP protocol - Redirecting a video call to mobile phone • Automatic search for cooperating devices in the local network • Support for devices with the ANPR vehicle identification functions and face recognition • Sectional speed measurement (requires several ANPR cameras on the road section) • The ability to track the person's location based on the face recognition function • Central management of the access control system : <ul style="list-style-type: none"> - Adding, deleting and editing users - Change of permissions of individual users and groups of users - Change of access to individual zones - Monitoring the status of individual doors - Central database management, updating and sharing the database between all system devices - It applies both to the classic databases of users of the access control system as well as to the bases of identified faces and vehicles • Advanced functions of the transition control : <ul style="list-style-type: none"> - Anti-passback - Remote opening of the door - Leaving the door open after the first access - Unlocking the transition only when more than one user is present - Remote access verification • Cooperation with the MNVR mobile recorders : <ul style="list-style-type: none"> - Archiving recordings from the mobile recorder using the local Wi-Fi network - Archiving the route covered by the vehicle with a mobile recorder - Access to the image recorded by the mobile recorder in real time (the recorder must have an Internet connection and a fixed IP address) • Emap function - possibility to mark the location of system elements on the map of the object : <ul style="list-style-type: none"> - The use of Google Maps - When an alarm is triggered, the element that initiated the alarm is marked on the map - Access to preview images from cameras and archived recordings from the map level - The camera's field of view can be marked on the map - Ability to roughly determine the route covered by a person based on face recognition function (required devices supporting face recognition functions) - Ability to roughly determine the vehicle route based on ANPR recognition (required cameras supporting this function) • Cooperation with the wall of monitors • Cooperation with the controllers of the NKS series • Integration with the alarm system : <ul style="list-style-type: none"> - Signaling of events registered on the server by alarm outputs - Setting the system arming schedules - Calling up the action after receiving the signal from the alarm control panel - Transmission of information about the triggered alarm to selected users • Intelligent image analysis : <ul style="list-style-type: none"> - Intelligent Object Tracking, people counting, heat map - Possibility to connecting in cascade - max. 5 levels, max. 20 devices - The possibility of redundant work
----------------------	---



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	100 ... 240 V AC	
Weight	19.1 kg	34 kg/km
Dimensions	445 x 522 x 133 mm -	
	RACK 19", 3U	
Supported languages	English	
Country of origin	China	
Manufacturer / Brand	DAHUA	
Guarantee	5 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00