





	RFID PROXIMITY CARD ATLO-307 13.56 MHz S50	SWITCH POE IP-8-20-L2 8-PORT ATTE	IP CAMERA IPC-F22P-D Wi-Fi BULLET 2C-D - 1080p 2.8 mm IMOU	CABLE N-W/N-W+RF5-10M
				
	0.48 EUR 0.48 EUR	244.95 EUR 244.95 EUR	37.03 EUR 37.03 EUR	20.45 EUR 20.45 EUR
Standard	TCP/IP	...
Standard	13.56 MHz S50
Sensor	1/2.8 " Progressive Scan CMOS	...
Compatibility	ISO/IEC 14443A
Matrix size	2.1 Mpx	...
Possibility of programming the serial number (ID)	—
Ability to write to internal memory	1 kB
Resolution	1920 x 1080 - 1080p	...
Cable	RF-5 : "N" Plug / "N" Plug
Serial Number overprint	—
Lens	2.8 mm	...
Impedance	50 Ω
View angle	102 °	...
Length of the cable	10 m
LAN ports	...	• 2 x RJ45 10/100/1000 Base-TX - Uplink, • 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE
Range of IR illumination	30 m	...
Management	...	—
Audio	• Microphone built-in, • Audio transmission via network	...
LED diodes	...	Power, LAN
Image compression method	H.265 / H.264	...
Main stream frame rate	25 fps @ 1080p	...
Network protocols	TCP, DHCP	...
Transmission speed	...	• 10 / 100 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 LAN ports
ONVIF	✓	...
Network interface	• Ethernet : 100 Mbps • Wi-Fi IEEE 802.11 b/g/n - 2.4 GHz	...
WEB Server	—	...

Mobile phones support	Access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU	...
Maximal output power	...	• 40 W @ Passive PoE - 1 ... 8 ports, • 30 W @ PoE (802.3at) - 1 ... 8 ports, • 15.4 W @ PoE (802.3af) - 1 ... 8 ports
Default admin user / password	admin / - The administrator password should be set at the first start	...
Maximal total power	...	96 W
Default IP address	DHCP	...
Web browser access ports	—	...
PC client access ports	—	...
Mobile client access ports	—	...
Port ONVIF	—	...
RTSP URL	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Main features	• Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) • Motion Detection • People detection • D-ZOOM - Digital Zoom : 16x	...
Power consumption	< 3.5 W	...
"Index of Protection"	IP67	...



Main features	Range : ~ 10 cm ,	<ul style="list-style-type: none"> • Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade @ 90 W • Built-in switching power supply : 48 V DC / 96 W • Efficiency : 92 % • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • Electronic fuse independently for each PoE channel • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement • "Index of Protection" : IP56 	...	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance
Power supply	...	• 190 ... 260 V AC - Built-in APS-90-480-OF switching mode power supply	12 V DC / 0.5 A (power adapter included)	...
Weight	0.005 kg	1.04 kg	0.24 kg	0.38 kg
Supported languages	—	...
Dimensions	86 x 54 x 0.8 mm	248 x 198 x 96 mm	148 x 74 x 74 mm	...
Manufacturer / Brand	ATLO	ATTE	DAHUA / IMOU	...
Guarantee	2 years	3 years	2 years	2 years