



	IP CAMERA IPC2312SB-ADF60KM-I0 - 1080p 6 mm UNIVIEW	MEASURING CONNECTOR 2-PIN LSA-W
		
	1059.30 PLN 1059.30 PLN	2.60 PLN 2.60 PLN
Number of pins	...	2 pcs
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	6 mm	...
View angle	<ul style="list-style-type: none"> • 54 ° (manufacturer data) • 53 ° (our tests result) 	...
Range of IR illumination	80 m	...
S/N ratio	> 52 dB	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	1/1	...
Audio	<ul style="list-style-type: none"> • Microphone built-in : 2 pcs • Audio transmission via network • Audio detection 	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
Port ONVIF	80	...

RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 580 mA 	...
Power consumption	≤ 7 W	...
Housing	Compact, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.5 kg	0.003 kg
Dimensions	206 x 74 x 74 mm	49 x 14 x 9.5 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	3 years	...