





	ACCESS CONTROLLER MC16-PAC-ST-1-KIT ROGER	TV OR MONITOR MOUNT AX-ORION RED EAGLE	MONITOR MOUNT BRATECK-LP41-44F	SMART LIGHT SWITCH ATLO-WB1-TUYA Wi-Fi, Tuya Smart
				
	567.06 AUD 567.06 AUD	28.24 AUD 28.24 AUD	12.46 AUD 12.46 AUD	18.86 AUD 18.86 AUD
Number of served transitions	1 (two-way)
Application	Works with lighting - switching on/off
Number of supported readers	4
Number of users	unlimited (purchase of the appropriate license required)
Rated voltage	100 ... 240 V AC, 50 / 60 Hz
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Buffer memory	8 000 000 events buffer
Maximum power	300 W (for each output)
Number of access zones	4
Rated current	max. 10 A
Mounting standard	...	VESA, 200 x 200, 300 x 200, 300 x 300, 400 x 200, 400 x 300, 400 x 400, 600 x 400	VESA 75, 100, 150, 200x100, 200, 300, 400x200, 400	...
Number of alarm zones	4
Number of buttons	1
Number of outputs	1
Screen size range	...	37 " ... 70 "	32 " ... 55 "	...
Battery backup support	12 V / 20 Ah
Connector type	screw terminals
Bearing capacity	...	40 kg	50 kg	...
Distance from mounting surface	...	33 mm	25 mm	...
Tilt adjustment	...	—
Horizontal rotation	...	—
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Rotation in the plane of the screen	...	± 3 °
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Metal housing • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication
Housing	Plastic
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Color	...	Black	Black	White
Operation temp	5 °C ... 40 °C	-20 °C ... 50 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)	≤ 80 %
Weight	3.9 kg	1.34 kg	0.94 kg	0.09 kg
Dimensions	405 x 365 x 120 mm	660 x 295 x 33 mm	438 x 425 x 26 mm	87 x 86 x 41 mm
Manufacturer / Brand	ROGER	RED EAGLE
Guarantee	3 years	2 years	2 years	2 years