



	<a href="#">ISOPROPYL ALCOHOL CLEANSER-IPA/100 BOTTLE 100 ml</a>	<a href="#">ACCESS CONTROL PANEL ACCO-NT2 SATEL</a>
		
	2.34 GBP 2.34 GBP	317.00 GBP 317.00 GBP
Package	Bottle 100 ml	...
Inputs	...	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>
Outputs	...	<ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>
Communication	...	<ul style="list-style-type: none"> <li>• 2 x RS-485</li> <li>• Expander bus - up to 32 expander modules</li> </ul>
Events memory	...	<ul style="list-style-type: none"> <li>• Events saving to the micro SD card (included)</li> <li>• Recording up to 1 000 000 events from the control panel,</li> <li>• Max. 100 000 events read from each access control module</li> </ul>
Users + admins	...	<ul style="list-style-type: none"> <li>• 8000 + 1</li> <li>• Max. 65 000 users in the whole ACCO NET system</li> </ul>
Output load	...	<ul style="list-style-type: none"> <li>• OC : 50 mA / 12 V DC</li> <li>• +EX : 0.5 A / 12 V DC</li> <li>• AUX : 0.5 A / 12 V DC</li> </ul>

Main features	...	<ul style="list-style-type: none"> <li>• Support for up to 255 access control modules</li> <li>• Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition)</li> <li>• Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway)</li> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Ability to assign 4 identifiers and a keyfob to a single user,</li> <li>• Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user,</li> <li>• Up to 256 access calendars, weekly schedules, daily schedules, time frames</li> <li>• Ability to control the control panel outputs by using keyfobs</li> <li>• Implementation of logic functions on inputs and outputs</li> <li>• Support for turnstiles</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> </ul>
Power supply	...	12 V DC / 140 mA (max)
Battery backup support	...	—
Operation temp	...	-10 °C ... 55 °C
Permissible relative humidity	...	93 % (non-condensing)
Weight	0.09 kg	0.096 kg
Dimensions	Ø 50 x 105 mm	151 x 69 x 17 mm
Manufacturer / Brand	...	SATEL
Guarantee	...	2 years