



	COAXIAL CABLE TRI-LAN-400 50 Ω	EXPANDER FPCX-ROX8R8T 16 OUTPUTS PYRONIX
		
	2.81 EUR 2.81 EUR	155.01 EUR 155.01 EUR
Number of outputs	...	16 pcs - programmable
In section	100 m . Price for 1m when buying a whole roll	...
Outputs type	...	<ul style="list-style-type: none"> • 8 pcs OC, • 8 pcs Relay
Tamper output	...	✓
Inner conductor	Ø 2.7 mm Cu ± 0.02 mm Wire	...
Load capacity of OC type programmable outputs	...	50 mA / 12 V DC
Dielectric	Ø 7.2 mm Physical foam	...
Relay switching current	...	max. 3 A DC
Relay switching voltage	...	max. 30 V DC
Shield	Foil - Al/PET	...
Current consumption (w/o OC type output load and w/o active relays)	...	25 mA
Protection class (Grade)	...	3
Braid	168 x Ø 0.15 mm Stranded wire CuSn	...
Power supply	...	9 V ... 15 V DC / 300 mA (max)
Impedance	50 Ω	...
Operation temp	...	-10 °C ... 50 °C
Outer coating	Ø 10.3 mm ± 0.20 mm PE	...
Weight	...	0.34 kg
Dimensions	...	174 x 26 x 32 mm
Manufacturer / Brand	...	PYRONIX
SAP Code	...	361300094
Manufacturer's code	...	PCX-ROX8R8T-P/BOX

Main features	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C 	...
Cable attenuation at 100m section	<p>Temperature : 20 °C</p> <p>2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz</p>	...
Maximum transmitted power	<p>3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz</p>	...
Guarantee	2 years	2 years

