





	CIRCUIT BREAKER HN-C25/3 THREE-PHASE 25 A C TYPE EATON	MULTI-PURPOSE AGENT K2-07/150ML SPRAY 150 ml K2	POWER METER WITH LCD DISPLAY UT-230B-EU UNI-T	RFID PROXIMITY CARD ATLO-307NR 13.56 MHz S50
				
	13.47 CHF 13.47 CHF	2.47 CHF 2.47 CHF	26.29 CHF 26.29 CHF	0.47 CHF 0.47 CHF
Standard	13.56 MHz S50
Compatibility	ISO/IEC 14443A
Package	...	Spray 150 ml
Possibility of programming the serial number (ID)	—
Device type	Circuit Breaker, Three-phase	...	Power meter with LCD display	...
Power measurement	0.1 ... 3680 W	...
Ability to write to internal memory	1 kB
Rated current	25 A
AC voltage measurement	100 ... 260 V	...
Serial Number overprint	✓
Number of poles	3
Maximal current	16 A	...
Tripping curves	C type
Maximal load	3680 W	...
Breaking capacity	6000 A
Range of displayed power	0.0 ... 9999 W	...
Range of displayed voltage	0.0 ... 9999 V	...
Rated voltage	• 230 V AC / 50 Hz • 400 V AC / 50 Hz
Connectors type	screw terminals
Range of displayed cumulative electricity	0.000 ... 9999 kWh	...
Cumulative cost of electricity	0.00 ... \$ 9999	...
Application	...	<ul style="list-style-type: none"> • Elimination of squeaks, • Lubrication, • Removal of water, • Penetration, • Corrosion protection, • Surface preservation, • Removal of dirt
Wire gauge	1 mm ² - 25 mm ²
Width in 17.5 mm modules	3

Main features	<ul style="list-style-type: none"> • Contact position indicator • Possibility of sealing 	<ul style="list-style-type: none"> • Spray formulation with a straw for easy application in hard-to-reach places • Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places • It can be used in any position, even upside down 	<ul style="list-style-type: none"> • Operation modes : Power consumption, Voltage, Cumulated amount of electricity, Cumulative cost of electricity, Cost of electricity (\$/kWh) • Large, readable LCD display • Simple configuration of the cost calculation setting 	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + 6H8D - Reverse number, • Range : ~ 10 cm, • The 6605 chip
Housing	Plastic, DIN, TS-35 rail mounting	...	Plastic	...
Security class	IP20	...
Socket type	F type (Schuko)	...
Power supply	230 V AC, 50 Hz + 1 x CR2032	...
Weight	0.316 kg	0.15 kg	0.165 kg	0.006 kg
Dimensions	52.5 x 84.5 x 73 mm	Ø 52 x 143 mm	130 x 65 x 80 mm	86 x 54 x 0.8 mm
Manufacturer / Brand	EATON	K2	UNI-T	ATLO
Guarantee	2 years	...	2 years	2 years