






	ROUTER ARCHER-C6 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK	BRACKET RG-AP180-MNT REYEE	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500CM-JL- A-0360B-S2 - 5 Mpx 3.6 mm DAHUA	POWER DISTRIBUTION UNIT PR-1.5M-4G-SW/B (4 OUTLETS) 1.3 m	SWITCH POE GTX- B1-26-242G 24-PORT
					
	60.45 CAD 60.45 CAD	84.40 CAD 84.40 CAD	135.03 CAD 135.03 CAD	6.23 CAD 6.23 CAD	361.43 CAD 361.43 CAD
Frequency range	2.4 GHz, 5 GHz
Rated voltage	220 ... 240 V AC / 50 Hz	...
In package	...	10 pcs The price for package
Total maximal current	10 A	...
Standard	AHD, HD-CVI, HD-TVI, CVBS
Application	...	RG-AP180
Maximal total load	2500 W	...
Sensor	Progressive Scan CMOS
Material	...	Plastic
Matrix size	5 Mpx
Antenna type	• 4 x Omnidirectional antenna - Integrated, • 1 x Internal antenna
Number of outlets	4 grounded outlets 10A/250V CEE 7/5	...
Fuse	—	...
Switch	✓	...
Wire gauge	3 x 1.5 mm ²	...
Standards	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Length of the cable	1.3 m	...
Baud rates	300 Mbps + 867 Mbps
Management	—
LAN ports	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink	• 24 x RJ45 (24 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
LED diodes	Power, PoE, Link/Act, Speed
LED indicators	Power, 2.4 GHz WLAN, 5 GHz WLAN, 4 x Ethernet, WAN, WPS
Transmission speed	• 10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink, • 10 / 100 Mbps : 24 x Port LAN & PoE
Resolution	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Lens	3.6 mm
Operation modes	• NOM - Normal - the device operates as normal PoE switch • VLAN - 1 ... 24 ports are isolated from each other and separately work with the 25, 26 ports • SUPM - Extend - Range : 250 m @ 10 Mbps

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

View angle	• 92 ° (manufacturer data) • 85 ° (our tests result)
Range of IR illumination	20 m
White light LED illuminator range	20 m
IR illuminator power adjustment	Automatic
Maximal output power	30 W / port PoE - 1 ... 24 ports
Maximal total power	300 W
MAC addresses table	8k
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Receiver sensitivity	2.4 GHz : • 11g 54M : -78 dBm • 11n HT20 : -74 dBm • 11n HT40 : -71 dBm 5 GHz : • 11a 6M : -93 dBm • 11a 54M : -78 dBm • 11ac HT20 : -69 dBm • 11ac HT40 : -65 dBm • 11ac HT80 : -62 dBm
DDNS	✓
DHCP server	✓
Audio	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only
Firmware update	✓
Certificates	CE, FCC Class B
OSD menu	✓
Protections	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding	Overvoltage ± 4 kV
Management interface	Web browser, TP-LINK Tether
Transmitter power	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz
Main features	• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
Power supply	12 V DC / 1 A (power adapter included)	...	12 V DC / 260 mA	...	100 ... 265 V AC
Power consumption	≤ 3.1 W
Housing	Compact - Metal	Plastic	...
Color	...	White	White	Black	...
"Index of Protection"	IP67
Vandal-proof	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	-40 °C ... 60 °C
Main features	<ul style="list-style-type: none"> • TP-Link OneMesh™ support • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • SSID hiding 	<ul style="list-style-type: none"> • Wall mounting • The product fits into mounting boxes compliant with US/EU standards 	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h
Operation temp	0 °C ... 40 °C	-10 °C ... 45 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.35 kg	0.15 kg	0.33 kg	0.28 kg	3.37 kg
Dimensions	257 x 161 x 215 mm	116 x 86 x 5 mm	167 x 70 x 70 mm	226 x 54 x 46 mm	440 x 290 x 45 mm, RACK 19", 1U
Manufacturer / Brand	TP-LINK	RUIJIE / REYEE	DAHUA
Guarantee	3 years	2 years	3 years	2 years	2 years